

MPZ5S40F

MINI PWR-ZONE DRY 1P 5KVA

480V-120/240V



Main

Product	Sealed Transformer
Certifications	UL Listed
Type	Mini Power-Zone
Enclosure Code	A
Insulation Temperature	365 °F (185 °C)
Phase	1 phase
Primary Voltage	480 V
Secondary Voltage	120/240 V
Full Capacity Taps	2 5 % FCBN
Power Rating	5 kVA
Temperature Rise	115 °C
Winding Material	Copper
Interrupt Rating	18 kA
Circuit Breaker Type	Primary main breaker Secondary main breaker Feeder breaker
Interior Type	QO Load Center interior
Number of Spaces Available	16
Number of Circuits	16
Enclosure Type	NEMA 3R hot-rolled steel

Complementary

Height	32.7 in (830.58 mm)
Width	12 in (304.80 mm)
Depth	11.9 in (302.26 mm)
Product Weight	135.00 lb(US) (61.235 kg)

Ordering and shipping details

Category	16275-MPZ PLUG ON BRANCH CB
Discount Schedule	PE2
GTIN	785901838944
Nbr. of units in pkg.	1
Package weight(Lbs)	139.00 lb(US) (63.049 kg)
Returnability	No
Country of origin	US

Packing Units

Unit Type of Package 1	PCE
Package 1 Height	17.30 in (43.942 cm)
Package 1 width	32.00 in (81.28 cm)
Package 1 Length	12.70 in (32.258 cm)
Unit Type of Package 2	PAL
Number of Units in Package 2	5
Package 2 Weight	876.79 lb(US) (397.704 kg)
Package 2 Height	40.00 in (101.6 cm)

Package 2 width	40.00 in (101.6 cm)
Package 2 Length	48.00 in (121.92 cm)

Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: Nickel (Metallic), which is known to the State of California to cause cancer, and Bisphenol A (BPA), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration
PVC free	Yes

Contractual warranty

Warranty	18 months
----------	-----------