



### Overview

Lead time	Usually Ships within 4 Weeks
-----------	------------------------------

### Main

Range	ClimaSys
Product name	CU
Product or Component Type	Cooling unit
Mounting type	Side
Type of Installation	Indoor
Product destination	For enclosure
Mounting Mode	By screws
Input voltage	230 V 50/60 Hz
Phase	1 phase
Cooling power	6820 Btu/H 50/60 Hz L35-L35 5150 Btu/h 50/60 Hz L35-L50

### Complementary

Height	39.33 in (999 mm)
Width	15.94 in (405 mm)
Depth	9.33 in (237 mm)
Line Rated Current	6.5 A
Inrush current	24 A
Power consumption in W	1080 W 50/60 Hz, L35-L35 1290 W 50/60 Hz, L35-L50
Energy efficiency ratio	1.9
Control Type	Electronic controller
Temperature setting range	68...122 °F (20...50 °C)
Ambient air temperature for operation	Maximum 122 °F (50 °C) Inside the enclosure 68...115 °F (20...46 °C) Outside the enclosure 68...122 °F (20...50 °C)
Noise level	65 dB
Pressure	362.59 psi (25 bar)
Flow rate	Internal circuit 227192.03 Gal/hr(US) (860 m3/h) 50/60 Hz External circuit 277385.62 Gal/hr(US) (1050 m3/h) 50/60 Hz
Net Weight	114.64 lb(US) (52 kg)
Cooling gas type	R134a 1.19 lb(US) (0.54 kg))
Type of filter	Optional external circuit filter
Protection type	Thermal protection T 10 A Short-circuit protection (magnetic)

Material	Steel
Color	Gray RAL 7035)

## Environment

Product Certifications	UL
Standards	DIN 3168
IP degree of protection	IP55 IEC 60529 on the internal circuit) IP34 IEC 60529 on the external circuit)

## Ordering and shipping details

Category	80036-ENCLOSURE SYSTEMS ACCESSORIES
Discount Schedule	ES1
GTIN	3606480653773
Nbr. of units in pkg.	1
Package weight(Lbs)	114.64 lb(US) (52.0 kg)
Returnability	Yes
Country of origin	US

## Packing Units

Unit Type of Package 1	PCE
Package 1 Height	9.33 in (23.7 cm)
Package 1 width	15.94 in (40.5 cm)
Package 1 Length	39.33 in (99.9 cm)
Unit Type of Package 2	P12
Number of Units in Package 2	5
Package 2 Weight	636.03 lb(US) (288.5 kg)
Package 2 Height	48.82 in (124.0 cm)
Package 2 width	31.50 in (80.0 cm)
Package 2 Length	47.24 in (120.0 cm)

## Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	<a href="#">REACH Declaration</a>
REACH free of SVHC	Yes
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
China RoHS Regulation	<a href="#">China RoHS Declaration</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
Circularity Profile	<a href="#">End Of Life Information</a>
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.