



Note:
- Drawings Not To Scale
- Drawings Subject to Change Without Notice
- Dimensions are inches next to [Millimeters]

Part No.:
JLL36250C



Schneider Electric United States
North American Division
Boston One Campus
800 Federal Street
Andover, MA 01810, USA
Phone: +1 877 342 5173
Email: CCC@us.schneider-electric.com

Technical Information:

General Application: Provides overload and short circuit protection
For Use With: Industrial Enclosures and Switchboards
Approvals: UL Listed - CSA Certified - IEC Rated
Mounting Type: Unit Mount
Terminal Type: Line: Lug - Load: Lug
Wire Size: #3/0-350 AWG/kcmil(Al/Cu)
Weight: 5 Pounds
Depth: 5.00 Inches
Height: 7.52 Inches
Width: 4.12 Inches

Description: PowerPact J-frame Thermal Magnetic Circuit Breaker
Number of Poles: 3-Pole
Ampere Rating: 250A
Voltage Rating: 600VAC/250VDC
Interrupting Rating: 125kA at 240VAC - 100kA at 480VAC - 50kA at 600VAC - 20kA at 250VDC
Circuit Breaker Rating: 100% Rated
Fixed AC Magnetic Trip: Low: 1250A - High: 2500A

Specification: