



### Main

|                            |                                                                  |
|----------------------------|------------------------------------------------------------------|
| Product                    | Sealed Transformer                                               |
| Certifications             | UL Listed                                                        |
| Type                       | Mini Power-Zone                                                  |
| Enclosure Code             | C                                                                |
| Insulation Temperature     | 365 °F (185 °C)                                                  |
| Phase                      | 3 phase                                                          |
| Primary Voltage            | 480 V                                                            |
| Secondary Voltage          | 208Y/120 V                                                       |
| Full Capacity Taps         | 2 5 % FCBN                                                       |
| Power Rating               | 15 kVA                                                           |
| Temperature Rise           | 115 °C                                                           |
| Winding Material           | Copper                                                           |
| Interrupt Rating           | 25 kA                                                            |
| Circuit Breaker Type       | Feeder breaker<br>Primary main breaker<br>Secondary main breaker |
| Interior Type              | QO Load Center interior                                          |
| Number of Spaces Available | 27                                                               |
| Number of Circuits         | 27                                                               |
| Enclosure Type             | NEMA 3R hot-rolled steel                                         |

### Ordering and shipping details

|                       |                             |
|-----------------------|-----------------------------|
| Category              | 16275-MPZ PLUG ON BRANCH CB |
| Discount Schedule     | PE2                         |
| GTIN                  | 785901385837                |
| Nbr. of units in pkg. | 1                           |
| Package weight(Lbs)   | 550.00 lb(US) (249.476 kg)  |
| Returnability         | No                          |

### Packing Units

|                        |                     |
|------------------------|---------------------|
| Unit Type of Package 1 | PCE                 |
| Package 1 Height       | 14.49 in (36.8 cm)  |
| Package 1 width        | 29.13 in (74 cm)    |
| Package 1 Length       | 46.26 in (117.5 cm) |

### Offer Sustainability

|                            |                                                                                                                                                                                                                                                                                                                                                              |
|----------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| California proposition 65  | WARNING: This product can expose you to chemicals including: Nickel (Metallic), which is known to the State of California to cause cancer, and Bisphenol A (BPA), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a> |
| RECh Regulation            |  <a href="#">RECh Declaration</a>                                                                                                                                                                                                                                         |
| RECh free of SVHC          | Yes                                                                                                                                                                                                                                                                                                                                                          |
| EU RoHS Directive          | Compliant  <a href="#">EU RoHS Declaration</a>                                                                                                                                                                                                                            |
| Mercury free               | Yes                                                                                                                                                                                                                                                                                                                                                          |
| RoHS exemption information |  Yes                                                                                                                                                                                                                                                                      |

|                             |                                                                                                                         |
|-----------------------------|-------------------------------------------------------------------------------------------------------------------------|
| China RoHS Regulation       |  <a href="#">China RoHS Declaration</a> |
| PVC free                    | Yes                                                                                                                     |
| <b>Contractual warranty</b> |                                                                                                                         |
| Warranty                    | 18 months                                                                                                               |