LV429413

Undervoltage release MN, ComPacT NSX, rated voltage 125VDC, screwless spring terminal connections





Main

Range	ComPacT
Device short name	MN
Product or Component Type	Voltage release
Device Application	Control
Range compatibility	ComPacT NSX new generation ComPacT NSX DC new generation ComPact NSX ComPact NSX DC EasyPact CVS PowerPact Multistandard
Voltage release type	Opening coil Undervoltage release
[Uc] control circuit voltage	125 V DC

Complementary

Operating threshold	0.350.7 x Un opening	
	0.85 x Un closing	
Response time	50 ms	
Supply holding power	5 W	
Supply inrush power	10 W	
Auxiliary connection terminal	Spring 0.000.00 in² (0.51.5 mm²) AWG 20AWG 16)	
Wire stripping length	0.28 in (7 mm)	

Ordering and shipping details

Category	01081-INTRA-COMPANY COMPONENTS	
Discount Schedule	NET	
GTIN	3606480019029	
Nbr. of units in pkg.	1	
Package weight(Lbs)	4.44 oz (126.0 g)	
Returnability	No	
Country of origin	PL	

Packing Units

Unit Type of Package 1	PCE
Package 1 Height	2.48 in (6.3 cm)
Package 1 width	1.57 in (4.0 cm)
Package 1 Length	3.23 in (8.2 cm)
Unit Type of Package 2	BB1
Number of Units in Package 2	10
Package 2 Weight	2.98 lb(US) (1.352 kg)
Package 2 Height	3.62 in (9.2 cm)
Package 2 width	5.91 in (15.0 cm)
Package 2 Length	8.86 in (22.5 cm)
Unit Type of Package 3	S03
Number of Units in Package 3	60

California proposition 65	WARNING: This product can expose you to chamicals including: DIND, which is	
Sustainable offer status	Green Premium product	
Offer Sustainability		
Package 3 Length	15.75 in (40.0 cm)	
Package 3 width	11.81 in (30.0 cm)	
Package 3 Height	11.81 in (30.0 cm)	
Package 3 Weight	18.85 lb(US) (8.55 kg)	

Sustainable offer status	Green Premium product	
California proposition 65	WARNING: This product can expose you to chemicals including: DINP, which is known to the State of California to cause cancer, and DIDP, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov	
REACh Regulation	REACh Declaration	
EU RoHS Directive	Compliant EPEU RoHS Declaration	
Mercury free	Yes	
RoHS exemption information	₫Yes	
China RoHS Regulation	China RoHS Declaration	
Environmental Disclosure	Product Environmental Profile	
Circularity Profile	End Of Life Information	
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.	
PVC free	Yes	

Contractual warranty

Contractual warranty		
Warranty	18 months	