8736SDG2V03

NEMA Starter, Type S, reversing, horizontal, Size 2, 45A, 25 HP at 575 VAC, 5 kA SSCR, 3 phase, 3 pole, melting alloy overload, 240 VAC coil, NEMA 1



Main

Product Type	Starter	
Product Range	S	
Starter Type	Reversing	

Complementary

Complementary		
NEMA Size	2	_
Rated Current	45 A	_
Number of Poles	3P	_
Mounting Orientation	Horizontal	_
Wiring Mode	3 wires	_
Maximum Voltage Rating	600 V AC	
Phase	3 phase	
Type of Overload	Melting alloy 3	
Horsepower Rating	10 HP 200 V AC 15 HP 230 V AC 25 HP 460 V AC 25 HP 575 V AC	
SCCR	Circuit-breaker: 5 kA at 600 V AC Fuse: 5 kA at 600 V AC	
Coil Voltage	220 V AC 50 Hz 240 V AC 60 Hz	_
Control Circuit Type	Common control circuit	_
Control Units	No control units	_
Pilot Light	Without pilot light	_
Auxiliary Contacts	Without	_
Terminal Type	Screw clamp terminals	_
Height	14.13 in (358.90 mm)	_
Width	14.88 in (377.95 mm)	_
Depth	7.66 in (194.56 mm)	_

Environment

Enclosure Type	NEMA 1 painted sheet steel
Certifications	UL Listed CSA

Ordering and shipping details

Category	21272-8702,36 SC,SD(NOT S*R,T,W)
Discount Schedule	CP1
GTIN	785901759522
Nbr. of units in pkg.	1
Package weight(Lbs)	33.00 lb(US) (14.969 kg)
Returnability	No
Country of origin	MX

Packing Units

Unit Type of Package 1	PCE	
Package 1 Height	14.13 in (35.9 cm)	
Package 1 width	14.88 in (37.8 cm)	
Package 1 Length	7.68 in (19.5 cm)	

Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
EU RoHS Directive	Not compliant
China RoHS Regulation	[™] China RoHS Declaration

Contractual warranty

Warranty	18 months
vvarianty	10 111011115
•	