



Main

Product	Power Outlet Panel
Marketing Trade Name	Servicepak
Amepre Rating	40 A
Short Circuit Current Rating	10 kA
Phase	1 phase
Voltage Rating	120 V AC

Complementary

Certifications	UL Listed
Application	Construction sites
Enclosure Rating	NEMA 3R
Electrical Connection	Screw clamp terminal
Wire Size	AWG 12...AWG 6 aluminium AWG 14...AWG 6 copper
Mounting	Surface
Outlet Configuration	2C

Ordering and shipping details

Category	00034-PAK DEVICES
Discount Schedule	DE4
GTIN	785901615934
Nbr. of units in pkg.	1
Package weight(Lbs)	9.04 lb(US) (4.10 kg)
Returnability	No
Country of origin	US

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
RECh Regulation	 RECh Declaration
RECh free of SVHC	Yes
EU RoHS Directive	Compliant  EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	 Yes
China RoHS Regulation	 China RoHS Declaration
Environmental Disclosure	 Product Environmental Profile

Contractual warranty

Warranty	18 months
----------	-----------