Product data sheet Characteristics

EMB3084

Square D - PowerLogic Energy Meter, Basic 800A, 2.45"X5.50" ID, 3CT's



Main

Range	PowerLogic
Product name	PowerLogic ENERGY METER
Product or Component Type	Energy meter
Device Application	Energy monitoring

Complementary

Type of measurement	Energy consumption Power Peak demand power Reactive power Power factor Voltage Current
Measurement accuracy	+/- 1 %
Measurement voltage	120 V AC between phase and neutral 240 V AC between phases
[Us] rated supply voltage	120 V AC - 2510 %
Network Frequency	50 Hz 60 Hz
Line Rated Current	800 A
Display Type	Backlit LCD
Display size	1.2 x 3.8 inch
Information displayed	Energy consumption Power Power maximum) Reactive power Power factor Voltage Current
Sampling rate	1280 Hz
Provided equipment	3 x current transformer
CT size	2.45 x 2.89 inch
Standards	ANSI C12.1
Product certifications	UL UL 3111-1 CUL
Width	7.60 in (193 mm)
Depth	Meter 2.99 in (76 mm)
Height	8.31 in (211 mm)

Environment

Isolation voltage	2500 V
Relative humidity	095 % non-condensing
Ambient air temperature for operation	32122 °F (050 °C)
Ambient Air Temperature for Storage	-40158 °F (-4070 °C)

Ordering and shipping details

Category	09779-POWERLOGIC ENERGY METER
Discount Schedule	PL1
GTIN	785901539377
Nbr. of units in pkg.	1
Package weight(Lbs)	10.3 lb(US) (4.67 kg)
Returnability	No
Country of origin	US

Offer Sustainability

California proposition 65	WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov
REACh Regulation	☑ REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Compliant EEU RoHS Declaration
Mercury free	Yes
RoHS exemption information	₫Yes
China RoHS Regulation	☑ China RoHS Declaration
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.

Contractual warranty