



### Main

Product	Power Outlet Panel
Marketing Trade Name	Servicepak
Amepre Rating	50 A
Short Circuit Current Rating	10 kA
Phase	1 phase
Voltage Rating	120 V AC

### Complementary

Certifications	UL Listed
Application	Recreational vehicle park sites
Enclosure Rating	NEMA 3R
Electrical Connection	Screw clamp terminal
Wire Size	AWG 12...AWG 6 aluminium AWG 14...AWG 6 copper
Mounting	Surface
Outlet Configuration	12C



### Ordering and shipping details

Category	00034-PAK DEVICES
Discount Schedule	DE4
GTIN	785901307839
Nbr. of units in pkg.	1
Package weight(Lbs)	9.32 lb(US) (4.228 kg)
Returnability	Yes
Country of origin	MX

### Packing Units

Unit Type of Package 1	PCE
Package 1 Height	6.40 in (16.256 cm)
Package 1 width	9.00 in (22.86 cm)
Package 1 Length	10.80 in (27.432 cm)

### Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a>
REACH Regulation	 <a href="#">REACH Declaration</a>
REACH free of SVHC	Yes
EU RoHS Directive	Compliant  <a href="#">EU RoHS Declaration</a>

Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	 <a href="#">Yes</a>
China RoHS Regulation	 <a href="#">China RoHS Declaration</a>
Environmental Disclosure	 <a href="#">Product Environmental Profile</a>

**Contractual warranty**

Warranty	18 months
----------	-----------