8903LH20V02C

8903L electrically held lighting contactor, 2 P, 2 NO, 30 A, 600 V, 110/120 V 50/60 Hz coil, NEMA 3R





Main Product or Component Electrically Held Lighting Contactor

Туре	
Range of Product	8903L
Control Circuit	Separate control circuit

Complementary

Complementary		
Control Circuit Voltage	110 V AC 50 Hz	
	120 V AC 60 Hz	
Inrush power in VA	150 VA 60 Hz	
	140 VA 50 Hz	
Hold-in power consumption in VA	30 VA 60 Hz	
	30 VA 50 Hz	
Current Rating	20 A tungsten	
	30 A fluorescent	
Number of Poles	2P 2 NO	
Control Unit	Selector switch HAND-OFF-AUTO)	
Pilot Light	No indicator	
Electrical Connection	Screw-clamp terminals	
Height	16.30 in (414 mm)	
Depth	8.62 in (219 mm)	
Width	9.84 in (250 mm)	

Environment

Enclosure Type	NEMA 3R painted sheet steel surface	
Product Certifications	UL Listed CSA	

Ordering and shipping details

Category	21321 - 8903 L (NOT LX)	
Discount Schedule	CP1	
GTIN	785901478751	
Nbr. of units in pkg.	1	
Package weight(Lbs)	22 lb(US) (9.98 kg)	
Returnability	No	
Country of origin	MX	

Offer Sustainability

Sustainable offer status	Green Premium product	
California proposition 65	WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov	
REACh Regulation	☑ REACh Declaration	
REACh free of SVHC	Yes	
EU RoHS Directive	Compliant EEU RoHS Declaration	
Toxic heavy metal free	Yes	
Mercury free	Yes	
RoHS exemption information	€Yes	
China RoHS Regulation	China RoHS Declaration	
Environmental Disclosure	Product Environmental Profile	
PVC free	Yes	
Halogen content performance	Halogen free plastic parts product	

Contractual warranty

Warranty	10	
vvarrantv	18 months	
Trainanty	TO INCITATIO	