## 8736SEG2V02S

NEMA Starter, Type S, reversing, horizontal, Size 3, 90A, 50 HP at 575 VAC, 5 kA SSCR, 3 phase, 3 pole, melting alloy overload, 120 VAC coil, NEMA 1



# Main Product Type Starter Product Range S Starter Type Reversing

Complementary

Complementary	
NEMA Size	3
Rated Current	90 A
Number of Poles	3P
Mounting Orientation	Horizontal
Wiring Mode	3 wires
Maximum Voltage Rating	600 V AC
Phase	3 phase
Type of Overload	Melting alloy 3
Horsepower Rating	25 HP 200 V AC 30 HP 230 V AC 50 HP 460 V AC 50 HP 575 V AC
SCCR	Circuit-breaker: 5 kA at 600 V AC Fuse: 5 kA at 600 V AC
Coil Voltage	110 V AC 50 Hz 120 V AC 60 Hz
Control Circuit Type	Separate control circuit
Control Units	No control units
Pilot Light	Without pilot light
Auxiliary Contacts	Without
Terminal Type	Screw clamp terminals
Height	29.16 in (740.66 mm)
Width	18.16 in (461.26 mm)
Depth	9.25 in (234.95 mm)

#### Environment

Enclosure Type	NEMA 1 painted sheet steel
Certifications	UL Listed CSA

### Ordering and shipping details

Category	21273-8702,36 SE,SF(NOT S*R,T,W)	
Discount Schedule	CP1	
GTIN	785901536000	
Package weight(Lbs)	87.81 lb(US) (39.830 kg)	
Returnability	No	
Country of origin	MX	

#### Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds which is known to the State of California to cause Carcinogen & Reproductive harm. For more information go to www.p65warnings.ca.gov
EU RoHS Directive	Not compliant
China RoHS Regulation	China RoHS Declaration

#### Contractual warranty

\A/=====+	40
vvarranty	18 months