

# Product data sheet

## Characteristics

# 8910DPA13V02U1

Contactor, Definite Purpose, 20A, 3 pole, 7.5 HP at 575 VAC, 3 phase, 110/120 VAC 50/60 Hz coil, open, UL Listed



## Main

Product or Component Type	Definite Purpose Contactor
Line Rated Current	20 A
Number of Poles	3P
Pole contact composition	3 NO
Range of Product	DPA

## Complementary

Maximum Horse Power Rating	1.5 Hp 115 V AC, 1 phase 3 Hp 230 V AC, 1 phase 7.5 Hp 230 V AC, 3 phase 7.5 Hp 460 V AC, 3 phase 7.5 hp 575 V AC, 3 phase
Locked rotor rated current	100 A 460 V AC 80 A 575 V AC 120 A 277 V AC
[Ue] rated operational voltage	600 V AC
[Uc] control circuit voltage	120 V AC 60 Hz 110 V AC 50 Hz
Phase	3 phase
Electrical Connection	Binder head

## Environment

Product Certifications	UL Listed CSA
------------------------	------------------

## Ordering and shipping details

Category	21341-8910 DPA 1_(20 AMP)
Discount Schedule	CP1B
GTIN	785901404354
Nbr. of units in pkg.	1
Package weight(Lbs)	16.64 oz (471.736 g)
Returnability	Yes
Country of origin	CN

## Packing Units

Unit Type of Package 1	PCE
Package 1 Height	2.60 in (6.604 cm)
Package 1 width	3.20 in (8.128 cm)
Package 1 Length	4.20 in (10.668 cm)

Offer Sustainability

REACH Regulation	<a href="#">REACH Declaration</a>
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
China RoHS Regulation	<a href="#">China RoHS Declaration</a>

Contractual warranty

Warranty	18 months
----------	-----------