



**Note:**  
 - Drawings Not To Scale  
 - Drawings Subject to Change Without Notice  
 - Dimensions are inches next to [Millimeters]

Part No.:  
**BGL26045LU**

**SQUARE D**  
 by **Schneider Electric**

Schneider Electric United States  
 North American Division  
 Boston One Campus  
 800 Federal Street  
 Andover, MA 01810, USA  
 Phone: +1 8773425173  
 Email: CCC@us.schneider-electric.com

**Technical Information:**

General Application: Provides overload and short circuit protection  
 Approvals: UL Listed - CSA Certified - IEC Rated  
 Mounting Type: Unit Mount  
 Terminal Type: ON end: EverLink Lugs with Control Wire Terminal / OFF end: EverLink Lugs  
 Weight: 2  
 Depth: 4.01  
 Height: 6.22  
 Width: 6.22  
 Mounting Height:

**Specification:**

Description: PowerPact B-Frame Thermal Magnetic Circuit Breaker  
 Number of Poles: 2-Pole  
 Ampere Rating: 045  
 Voltage Rating: 600Y VAC  
 Interrupting Rating: 65kA at240VAC 35kA at480VAC 18kA at600Y/347VAC  
 Circuit Breaker Rating: 80% Rated  
 Fixed AC Magnetic Trip: Hold: 400A - Trip: 600A