8536SBG2V06E

NEMA Motor Starter, Type S, nonreversing, Size 0, 18A, 5 HP at 460 VAC, up to 65 kA SCCR, 3 phase, 3 pole, bimetal, 480 VAC coil, NEMA 1



Main

Product Type	Motor starter
Product Range	S
Starter Type	Non reversing

Complementary

0	
18 A	
3P	
600 V AC	
3 phase	
IEC adapted Bi-metal	
3 HP 200 V AC 3 HP 230 V AC 5 HP 460 V AC 5 HP 575 V AC	
Circuit-breaker 35 A maximum, SCCR: 65 kA at 480 V AC Circuit-breaker 35 A maximum, SCCR: 50 kA at 600 V AC Fuse J 60 A maximum, SCCR: 65 kA at 600 V AC Fuse CC 60 A maximum, SCCR: 65 kA at 600 V AC	
440 V AC 50 Hz 480 V AC 60 Hz	
Common control circuit	
No control units	
Without pilot light	
Without	
Screw clamp terminals	
10.00 in (254.00 mm)	
6.00 in (152.40 mm)	
5.56 in (141.22 mm)	
	18 A 3P 600 V AC 3 phase IEC adapted Bi-metal 3 HP 200 V AC 3 HP 230 V AC 5 HP 460 V AC 5 HP 575 V AC Circuit-breaker 35 A maximum, SCCR: 65 kA at 480 V AC Circuit-breaker 35 A maximum, SCCR: 50 kA at 600 V AC Fuse J 60 A maximum, SCCR: 65 kA at 600 V AC Fuse CC 60 A maximum, SCCR: 65 kA at 600 V AC 440 V AC 50 Hz 480 V AC 60 Hz Common control circuit No control units Without pilot light Without Screw clamp terminals 10.00 in (254.00 mm) 6.00 in (152.40 mm)

Environment

Enclosure Type	NEMA 1 painted sheet steel
Certifications	UL Listed CSA NEMA

Ordering and shipping details

CP1
785901732402
1
7.14 lb(US) (3.239 kg)
Yes
MX

Packing Units

Unit Type of Package 1	PCE	
Package 1 Height	5.80 in (14.732 cm)	
Package 1 width	6.50 in (16.51 cm)	
Package 1 Length	11.50 in (29.21 cm)	

Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACh Regulation	☑ REACh Declaration
EU RoHS Directive	Not compliant
China RoHS Regulation	☑ China RoHS Declaration
PVC free	Yes

Contractual warranty

Contraction Warranty	
Warranty	18 months