



## Main

Product	Surge protection device
Surge Arrester Type	Electrical distribution network
Range	QO

## Complementary

Surge Current	20 kA
Voltage Rating	230 V AC
Number of Phases	1 phase
Wiring Configuration	3-wire
MCOV	270 V
Nominal Discharge Current	5 kA
Max Number of Poles	1
Height	2.89 in (73.5 mm)
Width	0.71 in (18 mm)
Depth	2.44 in (61.98 mm)

## Environment

Standards	IEC 61643-11
Ambient Operating	-40...176 °F (-40...80 °C)

## Ordering and shipping details

Category	08461-SURGE PROTECTION RESI
Discount Schedule	DE1B
GTIN	785901463269
Returnability	Yes
Country of origin	MX

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	2.91 in (7.4 cm)
Package 1 Width	0.71 in (1.8 cm)
Package 1 Length	2.44 in (6.2 cm)
Package 1 Weight	16.00 oz (453.592 g)

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

## Offer Sustainability

EU RoHS Directive	Compliant  <a href="#">EU RoHS Declaration</a>
Mercury free	Yes
RoHS exemption information	 <a href="#">Yes</a>
China RoHS Regulation	 <a href="#">China RoHS Declaration</a>