



FOR EASE OF PLUG INSERTION, IT IS
RECOMMENDED TO MOUNT RECEPTACLE
AT LEAST 48.00/[1219] ABOVE FLOOR

SQUARE D/SCHNEIDER ELECTRIC HAS PROPRIETARY RIGHTS TO THE INFORMATION CONTAINED
HEREON. THIS INFORMATION REMAINS THE PROPERTY OF SQUARE D/SCHNEIDER ELECTRIC
AND MAY BE REPRODUCED OR USED ONLY IN ACCORDANCE WITH INSTRUCTIONS OR
PERMISSION FROM SQUARE D/ SCHNEIDER ELECTRIC. THIS DOCUMENT SHALL BE RETURNED
TO SQUARE D/SCHNEIDER ELECTRIC UPON REQUEST. USER SHOULD VERIFY DRAWINGS ARE
THE MOST RECENT VERSION PRIOR TO USE.
2014, SCHNEIDER ELECTRIC, ALL RIGHTS RESERVED.

DUAL DIMENSIONS: INCHES
MILLIMETERS

RECEPTACLE MODULE FOR CONTROLLED PANELS
X-RAY/LASER POWER MODULE FROM SCHNEIDER ELECTRIC PROVIDE A CONVENIENT SOURCE OF POWER FOR PORTABLE
X-RAY AND LASER EQUIPMENT. THE RECEPTACLE PROVIDED IN EACH MODULE IS MATCHED TO THE NEMA PLUG
CONFIGURATION OF THE EQUIPMENT WITH WHICH IT WILL BE USED AND IS MOUNTED BEHIND THE DOOR ON THE
STAINLESS STEEL FACE PLATE. THE DOOR FEATURES A CONCEALED HINGED AND TOUCH LATCH.

REMOTE INDICATOR MODULE
SxRM1A2F

SQUARE D™
by **Schneider Electric**

DWG# SxRM1A2F
NO.