ZBVB34

Harmony XB4, Light block for head Ø22, white, integral LED, plug-in connector, 24 V AC/DC



Main Range of Product Harmony XB4 Harmony XB5 Product or Component Light block Type Device short name ZBV Sale per indivisible quantity Connections - terminals Plug-in connector Signalling type Steady Protected LED Light source Bulb base Integral LED Light block supply Direct Light source colour Green

24 V AC/DC 50/60 Hz

Complementary

Complementary		
Net Weight	0.04 lb(US) (0.016 kg)	
Supply voltage limits	19.230 V DC	
	21.626.4 V AC	
Current Consumption	18 mA	
Service life	100000 h at rated voltage and 25 °C	
Surge withstand	1 kV IEC 61000-4-5	
Mounting of block	Front mounting	
Electrical composition code	M1	
	M2	
	M3	
	M4	
	M5	
	M6	
	M10	
	MF1	
	P1	
	P2	
	PF1	

[Us] rated supply

voltage

Environment

LIMIOIIIICII	
Protective treatment	ТН
Ambient Air Temperature for Storage	-40158 °F (-4070 °C)
Ambient Air Temperature for Operation	-40158 °F (-4070 °C)
IP degree of protection	IP20 IEC 60529
Standards	EN/IEC 60947-5-4 JIS C8201-5-1 UL 508 CSA C22.2 No 14 EN/IEC 60947-1 EN/IEC 60947-5-1 EN/IEC 60947-5-5 JIS C8201-1
Resistance to fast transients	2 kV IEC 61000-4-4
Resistance to electromagnetic fields	9.14 V/m (10 V/m) IEC 61000-4-3
Resistance to electrostatic discharge	6 KV on contact (on metal parts) IEC 61000-4-2 8 kV in free air (in insulating parts) IEC 61000-4-2
· · · · · · · · · · · · · · · · · · ·	

Electromagnetic emission	Class B IEC 55011	
[Us] rated supply voltage	24 V	
Ordering and shipping details		
Category	22469-PUSHBUTTON,22MM ACCESSORIES-NEW	
Discount Schedule	CS2	
GTIN	3389110090154	
Returnability	Yes	
Country of origin	FR	
Packing Units		
Unit Type of Package 1	PCE	
Number of Units in Package 1	1	
Package 1 Height	2.20 in (5.6 cm)	
Package 1 Width	1.73 in (4.4 cm)	
Package 1 Length	2.13 in (5.4 cm)	
Package 1 Weight	0.28 oz (8.0 g)	
Unit Type of Package 2	S02	
Number of Units in Package 2	200	
Package 2 Height	5.91 in (15.0 cm)	
Package 2 Width	11.81 in (30.0 cm)	
Package 2 Length	15.75 in (40.0 cm)	
Package 2 Weight	4.71 lb(US) (2.135 kg)	
Unit Type of Package 3	CAR	
Number of Units in Package 3	5	
Package 3 Height	2.20 in (5.6 cm)	
Package 3 Width	1.73 in (4.4 cm)	
Package 3 Length	2.13 in (5.4 cm)	
Package 3 Weight	1.48 oz (42.0 g)	

Offer Sustainability

Sustainable offer status	Green Premium product	
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov	
REACh Regulation	REACh Declaration	
REACh free of SVHC	Yes	
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration	
Mercury free	Yes	
RoHS exemption information	₫Yes	
China RoHS Regulation	China RoHS Declaration	
Environmental Disclosure	Product Environmental Profile	
Circularity Profile	☑ End Of Life Information	
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.	

Contractual warranty


	,
Warranty	18 months

Product data sheet Dimensions Drawings

ZBVB34

Dimensions

with ZB5AZ009 Fixing Collar



with ZB4BZ009 Fixing Collar

