


Product data sheet

Specifications



Terminal block, Linergy, fuse holder, Class H, 30A, 600 V, 3 pole

9080FB3611

Product availability : Stock - Normally stocked in distribution facility

Price* : 81.00 USD

Main

Range	9080FB
Product	Fuse holder

Complementary

Current Rating	30 A
[Ue] rated operational voltage	<= 600 V AC/DC
Fuse type	H
Fuse size	0.8125 x 5 in
Number of poles	3
Electrical Connection	Pressure wire clamp
Wire Gauge	AWG 14...AWG 10 copper or aluminium
SCCR	10 kA UL 512
Product Certifications	CE CSA file 70360 class 6225 01 UL listed file E40747 CCN IZLT
Operating Temperature	-40...302 °F (-40...150 °C)
Mounting Type	Surface mount
Block Material	Phenolic block
Wire stripping length	0.4375 in (11.11 mm)
Terminal Tightening Torque	screw terminals 25 lbf.in (2.82 N.m) AWG 14...AWG 10 copper
Height	6.25 in (158.75 mm)
Width	4.25 in (107.95 mm)
Depth	1.69 in (42.93 mm)

Ordering and shipping details

Category	21701-9080 FB
Discount Schedule	CP1
GTIN	785901097112
Returnability	Yes

* Price is “List Price” and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Country of origin	US
-------------------	----

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	1.60 in (4.064 cm)
Package 1 Width	4.30 in (10.922 cm)
Package 1 Length	6.20 in (15.748 cm)
Package 1 Weight	10.40 oz (294.835 g)

Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)

Contractual warranty

Warranty	18 months
----------	-----------

Recommended replacement(s)