

Low voltage transformer, encapsulated buck boost, 1 phase, 0.1kVA, 240x480V primary, 24/48V secondary, Type 3R

100SV82A

Product availability: Stock - Normally stocked in distribution

facility

Price\*: 568.50 USD

### Main

Product	Buck and Boost Transformer
Enclosure Code	2A
Enclosure Type	NEMA 3R
Insulation Temperature	221 °F (105 °C)
Primary Voltage	240 x 480 V
Power Rating	0.1 kVA
Secondary Voltage	24/48 V
Temperature Rise	55 °C

## Ordering and shipping details

Category	16265-BUCK & BOOST
Discount Schedule	PE2
GTIN	785901703044
Returnability	Yes
Country of origin	US

# **Packing Units**

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	6.70 in (17.02 cm)
Package 1 Width	6.70 in (17.02 cm)
Package 1 Length	7.90 in (20.07 cm)
Package 1 Weight	6.55 lb(US) (2.97 kg)

## Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Phenyl glycidyl ether, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov

<sup>\*</sup> Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

REACh Regulation	REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile
PVC free	Yes

Warranty 18 months

Recommended replacement(s)