

Terminal block, Linergy, box lug connector, orange colored block, 30A, 600 V

9080GMS6

Product availability: Stock - Normally stocked in distribution facility

Price*: 2.70 USD

Main

mam	
Range of Product	9080G
Product Type	Terminal block
Localisation on Device	Standard
Color	Orange
Quantity	Set of 50

Complementary

Complementary	
Voltage Rating	600 V AC/DC
Current Rating	30 A UL 30 A CSA
Wire Size	AWG 22AWG 10 copper
Mounting Type	35 mm DIN rail 9080GH track
Certifications	UL recognized E60616 CCN XCFR2 CE CSA file 62144 class 6228 01
Protection Type	Fingersafe DIN 57470
Electrical Connection	Zinc plated steel box lugs
Material	Nylon block Tin plated brass busbar
Ambient Air Temperature for Operation	-40257 °F (-40125 °C)
Electrical Connrection Tightening Torque	Lug zinc plated steel 78 lbf.in (0.790.90 N.m) : AWG 22AWG 10 copper)
Height	1.82 in (46.23 mm)
Width	1.72 in (43.69 mm)
Depth	0.235 in (5.97 mm)
Density	51 per foot
Compatible End Barrier	GM6B

Ordering and shipping details

Category 21702-9080 G (NOT GCB)

^{*} Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Discount Schedule	CP5
GTIN	785901743255
Returnability	No
Country of origin	MX
Packing Units	
Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	0.30 in (0.762 cm)
Package 1 Width	1.80 in (4.572 cm)
Package 1 Length	1.70 in (4.318 cm)
Package 1 Weight	0.32 oz (9.072 g)
Offer Sustainability	
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACh Regulation	REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration
· ·	Pro-active China RoHS declaration (out of China RoHS legal scope)

Contractual warranty

Warranty 18 months

Recommended replacement(s)