



WIRING DIAGRAMS

NOT FUSIBLE



TERMINAL LUGS

AMPERES	MAX. WIRE	MIN. WIRE	TYPE
30	#6 AWG	#12 AWG	AL
30	#6 AWG	#14 AWG	CU

NEMA TYPE 12/3R

DUAL DIMENSIONS: INCHES
MILLIMETERS

CATALOG NUMBER	VOLTAGE RATINGS	AMPERAGE RATINGS	HORSEPOWER RATINGS					
			240VAC		480VAC		600VAC	
			MAX.		MAX.		MAX.	
HU361AWKEI4MVW	600VAC;600VDC	30	1 Ø	3 Ø	1 Ø	3 Ø	1 Ø	3 Ø
			5 ▲	10	7 1/2 ▲	20	10 ▲	30
							5 ▲	15 ▲

NOTES:
 CULUS LISTED - E2875
 FINISH - GRAY BAKED ENAMEL
 WHEN MOUNTING THESE SWITCHES, ALLOW 3.00 IN / 76 MM MIN.
 CLEARANCE BETWEEN ENCLOSURES FOR OPENING OF SIDE HINGED DOOR.
 ▲ USE BOTH OUTER SWITCHING POLES
 SWITCH INCLUDES (2) FACTORY INSTALLED ELECTRICAL INTERLOCKS, CAT. NO. EIK034M.

HEAVY DUTY SAFETY SWITCHES
 VISIBLE BLADE TYPE
 30 AMPERE-SERIES F6
 ENCLOSURE - NEMA TYPE 12/3R
 WITH (2) EIK034M



SQUARE D COMPANY

DWG# 3322
 NO.