



TERMINAL LUG DATA			
AMPERES	MAX WIRE	MIN WIRE	TYPE
400	(1) 600 KCMIL	(1) 1/0 AWG	AL/CU
	OR (2) 300 KCMIL	OR (2) 1/0 AWG	

SEISMIC NOTES:
USE (4) 3/8" DIA GRADE 5 STEEL MOUNTING BOLTS @ HOLES AA
MAX CONFIGURED WEIGHT 155 LB (AWK CATALOG NUMBERS)
157 LB (DS CATALOG NUMBERS) FOR THE PURPOSE OF DETERMINING
SEISMIC ANCHORAGE REQUIREMENTS. FOR ALL OTHER APPLICATIONS,
CONTACT SCHNEIDER ELECTRIC.

DUAL DIMENSIONS: INCHES
MILLIMETERS

NOTES:
FINISH - NEMA TYPE 12 GRAY BAKED ENAMEL
NEMA TYPE 4, 4X, 5 TYPE 304 STAINLESS STEEL
UL LISTED - FILE E-154828
ALL NEUTRALS - INSULATED GROUNDABLE
SUITABLE FOR USE AS SERVICE EQUIPMENT
SHORT CIRCUIT CURRENT RATINGS:
10,000 AMPERES WHEN USED WITH OR PROTECTED BY CLASS H OR K FUSES.
200,000 AMPERES WHEN USED WITH OR PROTECTED BY CLASS R FUSES HAVING
CLASS REJECTIONS KITS INSTALLED OR CLASS J FUSES.
NEUTRAL ASSEMBLY H600SNC MUST BE USED FOR 480VAC, CORNER GROUNDED DELTA SYTEM.
*FOR CORNER GROUNDED DELTA SYSTEMS ONLY WITH SOLID NEUTRAL ASSEMBLY INSTALLED.

CATALOG NUMBER		VOLTAGE RATINGS	WIRING DIAG	HORSEPOWER RATINGS				
NEMA TYPE 12	NEMA TYPE 4,4X,5 STAINLESS STEEL			240VAC		480VAC		250 VDC
				STD	MAX	STD	MAX	
				3Ø	3Ø	3Ø	3Ø	
H225AWK	H225DS	240VAC;250VDC	A	—	—	—	—	50
H225NAWK	H225NDS	240VAC;250VDC	B	50*	125*	—	—	—
H265AWK	H265DS	600VAC;600VDC	A	—	—	100*	250*	50
HU265AWK	HU265DS	600VAC;600VDC	C	—	—	—	—	50

HEAVY DUTY SAFETY SWITCHES
VISIBLE BLADE TYPE
400 AMPERE
ENCLOSURE - NEMA TYPE 12
NEMA TYPE 4, 4X, 5 STAINLESS STEEL



DWG# 1927S
NO.