

Product data sheet

Specifications



NEMA Combination Starter, Type S,
60A fusible disconnect, Size 1, 27A,
melting alloy overload, 120 VAC coil,
NEMA 3R/12

8538SCASP2

Product availability : Stock - Normally stocked in distribution facility

Price* : 3,615.00 USD

Main

Product	Combination Starter
Type	S
Control Circuit Type	Separate control circuit

Complementary

Control Circuit Voltage	110 V AC 50 Hz 120 V AC 60 Hz
Starter Type	Non reversing
Line Rated Current	27 A
Number of Poles	3P
Horsepower Rating	7.5 hp 200 V AC, 3 phase 7.5 hp 230 V AC, 3 phase
Maximum Voltage Rating	600 V AC
Control Units	Selector switch HAND-OFF-AUTO)
Pilot Light	Red indicator on LED Green indicator off LED
Auxiliary Contacts	2 NO + 2 NC
Thermal overload type	Melting alloy 3
Disconnect Type	Fusible disconnect switch H and K, 60 A, electrical SPDT
NEMA size	1
Height	24 in (609.60 mm)
Depth	8.34 in (211.84 mm)
Width	9.5 in (241.30 mm)
Handle Swing	3.25 in (82.55 mm)

Environment

Enclosure Type	NEMA 12 painted sheet steel with external reset
Product Certifications	UL Listed CSA

* Price is “List Price” and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Ordering and shipping details

Category	21213-8538,39 SC,SD(NOT S*R,T,W)
Discount Schedule	CP1
GTIN	785901863137
Returnability	No
Country of origin	MX

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	10.60 in (26.924 cm)
Package 1 Width	13.10 in (33.274 cm)
Package 1 Length	28.80 in (73.152 cm)
Package 1 Weight	39.61 lb(US) (17.967 kg)

Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACH Regulation	REACH Declaration
EU RoHS Directive	Not compliant
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information.

Contractual warranty

Warranty	18 months
----------	-----------

Recommended replacement(s)