HOM1632L225PRB

Load center, Homeline, 1 phase, 16 spaces, 32 circuits, 225A convertible main lugs, PoN, NEMA3R





Main

Product Type	Load Center
Marketing Trade Name	Homeline
Load Center Type	PoN Convertible Mains (lugs)
Rated Current	225 A
Number of Spaces	16
Maximum Number of Single Pole Circuits	32
Enclosure Rating	NEMA 3R outdoor
Cover Type	Surface cover
Electrical Connection	Lugs

Complementary

Mar Obert Ober 10 and Define	40.14
Max Short Circuit Current Rating	10 kA
Maximum Number of Tandem Breakers	16
Number of Phases	1 phase
Voltage Rating	120/240 V AC
Wire Size	AWG 4250 kcmil copper AWG 4300 kcmil aluminium
Ground Bar	Grounding bar (ordered separately)
Wiring Configuration	3-wire
Busbar Material	Tin plated aluminium busbar
Enclosure Material	Welded galvannealed steel
Surface Finish	Baked enamel Gray
Box Number	6R
Height	29.84 in (758 mm)
Width	14.76 in (375 mm)
Depth	4.53 in (115 mm)

Environment

Ambient Air Temperature for Operation	23 °F (-5 °C) 104 °F (40 °C)	of sollows
Product Certifications	UL listed file E-6294	

Ordering and shipping details

Category	00145-HOM LC&CVR,12-42CKT NEMA3R
Discount Schedule	DE3C
GTIN	785901860877
Returnability	Yes
Country of origin	US

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	4.80 in (12.192 cm)
Package 1 Width	15.60 in (39.624 cm)
Package 1 Length	31.80 in (80.772 cm)
Package 1 Weight	38.70 lb(US) (17.554 kg)

Offer Sustainability

WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to
www.P65Warnings.ca.gov
REACh Declaration
Yes
Compliant EPEU RoHS Declaration
Yes
Yes
₫Yes
China RoHS Declaration
Product Environmental Profile