

Product data sheet

Characteristics

8903SMA71V02

Contactor, Type S, combination lighting, mechanically held, 30A, 3 pole, 600 V fuse, 110/120 VAC 50/60 Hz coil, NEMA 12



Main

Product	Combination mechanically held lighting contactor
Type	S

Complementary

Control Circuit Voltage	120 V AC 60 Hz 110 V AC 50 Hz
Current Rating	30 A
Number of Poles	3P
Control Units	No control units
Pilot Light	Without pilot light
Auxiliary Contacts	Without
Other Options	None
Disconnector device type	Fusible disconnect switch R, 30 A 600 V
Electrical Connection	Lugs
Height	12.76 in (324 mm)
Depth	8.54 in (217 mm)
Width	6.38 in (162 mm)

Environment

Enclosure Type	NEMA 12/3R painted sheet steel surface none
Product Certifications	UL listed file E16151 CCN NRNT

Ordering and shipping details

Category	21324 - 8903 S (NOT S*C) MECH.
Discount Schedule	CP1
GTIN	785901764304
Returnability	No
Country of origin	MX

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	12.76 in (32.4 cm)
Package 1 Width	6.38 in (16.2 cm)
Package 1 Length	8.54 in (21.7 cm)
Package 1 Weight	28.95 lb(US) (13.131 kg)

Offer Sustainability

EU RoHS Directive

Under investigation

Contractual warranty

Warranty

18 months
