HU361NDS

Safety switch, heavy duty, non fusible, 30A, 3 poles, 30 hp, 600 VAC/DC, NEMA 4, 4X, 5, 304 steel, neutral,





Main

Product	Single Throw Safety Switch
Duty Rating	Heavy duty
Device Application	Heavy application
Disconnect Type	Non-fusible disconnect
Factory Installed Neutral	Neutral (factory installed)
Phase	3 phase
Number of Poles	3
Voltage Rating	600 V AC/DC
Enclosure Rating	NEMA 4/4X/5 stainless steel 304
Motor power hp	2 Hp at 120 V AC 50-60 Hz for 1 phase motors 5 Hp at 240 V AC 50-60 Hz for 1 phase motors 10 Hp at 240 V AC 50-60 Hz for 3 phase motors 7.5 Hp at 480 V AC 50-60 Hz for 1 phase motors 20 Hp at 480 V AC 50-60 Hz for 3 phase motors 10 Hp at 600 V AC 50-60 Hz for 1 phase motors 30 Hp at 600 V AC 50-60 Hz for 3 phase motors 3 Hp at 125 V DC 5 Hp at 250 V DC 15 hp at 600 V DC

Complementary

Mounting Type	Surface
Wiring configuration	4-wire (3PH + N)
Wire Size	AWG 12AWG 6 aluminium AWG 14AWG 6 copper
Tightening torque	45 Lbf.In (5.08 N.m) 0.02 in² (13.3 mm²) (AWG 6) 40 Lbf.In (4.52 N.m) 0.01 in² (8.367 mm²) (AWG 8) 35 lbf.in (3.95 N.m) 0.000.01 in² (2.065.261 mm²) (AWG 14AWG 10)
Depth	5.11 in (129.79 mm)
Width	8.67 in (220.22 mm)
Height	14.93 in (379.22 mm)

Environment

Certifications UL listed file E2875	Certifications	
-------------------------------------	----------------	--

Ordering and shipping details

Category	00010-H&HU SW,2&3P,N4,SS,30-200A	
Discount Schedule	DE1	
GTIN	785901666264	
Returnability	No	
Country of origin	US	

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	5.12 in (13 cm)
Package 1 Width	8.66 in (22 cm)
Package 1 Length	14.92 in (37.9 cm)
Package 1 Weight	13.37 lb(US) (6.065 kg)

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACh Regulation	[™] REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Compliant EEU RoHS Declaration
Mercury free	Yes
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	€Yes
Environmental Disclosure	Product Environmental Profile
PVC free	Yes

Contractual warranty

	•
Warranty	18 months