Q0112L125PWG

Load center, QO, 1 phase, 12 spaces, 12 circuits, 125A convertible main lugs, PoN, NEMA1, wide gutter, UL





Main

Marketing Trade Name	QO
Product Type	Load Center

Complementary

Complementary		
Tightening Torque	Cover 20 lb.in	
PoN Convertible Mains (lugs)	PoN Convertible Mains (lugs)	
Rated Current	125 A	
Number of Spaces	12	
Max Short Circuit Current Rating	65 kA	
Maximum Number of Single Pole Circuits	12	
Maximum Number of Tandem Breakers	12	
Number of Phases	1 phase	
Ground Bar	Grounding bar (ordered separately)	
Box Number	14	
Height	20.92 in (531.37 mm)	
Width	14.25 in (361.95 mm)	
Depth	3.75 in (95.25 mm)	

Environment

Enclosure Rating	NEMA 1 indoor	
Ambient Air Temperature for Operation	23 °F (-5 °C) 104 °F (40 °C)	
Product Certifications	UL Listed	

Ordering and shipping details

Category	10003-QO PON 1PH LC,12-60 CKT, ML N1
Discount Schedule	DE3A
GTIN	785901583172
Returnability	No

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	20.91 in (53.1 cm)
Package 1 Width	14.25 in (36.2 cm)
Package 1 Length	3.74 in (9.5 cm)
Package 1 Weight	15.00 lb(US) (6.804 kg)

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACh Regulation	REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Compliant EPEU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	₫Yes
China RoHS Regulation	☑ China RoHS Declaration
Environmental Disclosure	Product Environmental Profile
	— 1 Todad Elitholimolia 1 Tolio