



TERMINAL LUG DATA ‡			
AMPERES	MAX WIRE	MIN WIRE	TYPE
100	#1/0 AWG	#12 AWG	AL
100	#1/0 AWG	#14 AWG	CU

DUAL DIMENSIONS: INCHES
MILLIMETERS

NOTES:
 FINISH — TYPE 316 STAINLESS STEEL
 UL LISTED — E2875
 CSA — FILE PER REFERENCE 158337 REPORT 1100887 (LL 89067-17)
 ALL NEUTRALS — INSULATED
 SHORT CIRCUIT CURRENT RATINGS:
 10,000 RMS SYMMETRICAL AMPERES
 WHEN USED IN CONJUNCTION
 WITH CLASS H OR K FUSES
 200,000 RMS SYMMETRICAL AMPERES WHEN USED
 IN CONJUNCTION WITH CLASS R, J OR T FUSES
 * USE OUTER SWITCHING POLES
 ♦ IF CORNER GROUNDED DELTA SYSTEMS, INSTALL NEUTRAL AND USE OUTER SWITCHING
 POLES FOR UNGROUNDED CONDUCTORS.
 ▲ NOT FOR CORNER GROUNDED DELTA SYSTEMS.
 ‡ LUGS SUITABLE FOR 60°C OR 75°C CONDUCTORS ONLY.

CATALOG NUMBER	VOLTAGE RATINGS	AMPERAGE RATINGS	WIRING DIAG	HORSEPOWER RATINGS																250 VDC		600 VDC			
				240VAC						480VAC						600VAC									
				STD			MAX			STD			MAX			STD			MAX						
				1Ø	2Ø	3Ø	1Ø	2Ø	3Ø	1Ø	2Ø	3Ø	1Ø	2Ø	3Ø	1Ø	2Ø	3Ø	1Ø	2Ø	3Ø				
H363SS	600VAC,600VDC	100	A	—	—	—	—	—	—	10*	—	25♦	30*	—	60♦	—	—	30	—	—	75	—	—	40*	50*
HU363SS	600VAC,600VDC	100	B	—	—	—	20*	—	40♦	—	—	—	40*	—	75▲	—	—	—	40*	—	100	—	20*	—	50*

HEAVY DUTY SAFETY SWITCHES
 VISIBLE BLADES
 100 AMPERE—SERIES F6
 ENCLOSURE—NEMA TYPE 4, 4X AND 5 STAINLESS STEEL



DWG# 3332
NO.