# 8538SBG11V81FF4T

NEMA Combination Starter, Type S, nonfusible disconnect, Size 0, 18A, 5 HP at 600 VAC polyphase, 120 VAC coil, NEMA 1



#### Main

Product	Combination Starter
Туре	S
Control Circuit Type	Control circuit transformer

### Complementary

Control Circuit Voltage	120 V AC 60 Hz secondary circuit	
	480 V AC 60 Hz primary circuit	
Starter Type	Non reversing	
Number of Poles	3P	
Horsepower Rating	3 Hp 200 V AC, 3 phase	
	3 Hp 230 V AC, 3 phase	
	5 Hp 460 V AC, 3 phase	
	5 hp 575 V AC, 3 phase	
Maximum Voltage Rating	600 V AC	
Control Units	No control units	
Pilot Light	No indicator	
Auxiliary Contacts	Without	
Control Circuit Fusing	2 fuses primary circuit	
	1 fuse secondary circuit	
Thermal overload type	Melting alloy 3	
Disconnect Type	Non-fusible disconnect switch	
NEMA size	0	

## Environment

Enclosure Type	NEMA 1 painted sheet steel with external reset

#### Ordering and shipping details

Category	21212 - 8538,39SB(NOT S*R,S*T,S*W)
Discount Schedule	CP1
GTIN	785901662754
Returnability	No
Country of origin	MX

#### **Packing Units**

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	45.00 lb(US) (20.412 kg)

# Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACh Regulation	☑ REACh Declaration
EU RoHS Directive	Not compliant
China RoHS Regulation	China RoHS Declaration

### Contractual warranty

Warranty	18 months
----------	-----------