# HU364RB

Safety switch, heavy duty, non fusible, 200A, 3 wire, 3 poles, 150hp, 600VAC/DC, Type 3R, bolt on hub provision





### Main

Product	Single Throw Safety Switch	
Duty Rating	Heavy duty	
Device Application	Heavy application	
Disconnect Type	Non-fusible disconnect	
Factory Installed Neutral	None	
Phase	3 phase	
Number of Poles	3	
Current Rating	200 A	
Voltage Rating	600 V AC/DC	
Enclosure Rating	NEMA 3R galvannealed steel	
Motor power hp	15 Hp at 240 V AC 50-60 Hz for 1 phase motors 60 Hp at 240 V AC 50-60 Hz for 3 phase motors 50 Hp at 480 V AC 50-60 Hz for 1 phase motors 125 Hp at 480 V AC 50-60 Hz for 3 phase motors 50 Hp at 600 V AC 50-60 Hz for 1 phase motors 150 Hp at 600 V AC 50-60 Hz for 3 phase motors 40 Hp at 250 V DC 50 hp at 600 V DC	

### Complementary

Mounting Type	Surface	
Electrical Connection	Lugs	
Wiring configuration	3-wire	
Wire Size	AWG 6250 kcmil copper or aluminium	
Tightening torque	275 lbf.in (31.07 N.m) 0.020.20 in² (13.3127 mm²) (AWG 6250 kcmil)	
Depth	8.5 in (215.90 mm)	
Width	18.63 in (473.20 mm)	
Height	29.25 in (742.95 mm)	
Net Weight	53.00 lb(US) (24.04 kg)	

#### Environment

Certifications	UL listed file E2875

## Ordering and shipping details

Category	00009-H&HU SW,2&3P,N3R,30-200A	
Discount Schedule	DE1	
GTIN	785901505631	
Returnability	No	
Country of origin	US	

## **Packing Units**

Unit Type of Package 1	PCE	
Number of Units in Package 1	1	
Package 1 Height	8.30 in (21.082 cm)	
Package 1 Width	19.30 in (49.022 cm)	
Package 1 Length	30.80 in (78.232 cm)	
-		

Package 1 Weight	42.00 lb(US) (19.051 kg)
Unit Type of Package 2	PAL
Number of Units in Package 2	15
Package 2 Height	45.20 in (114.808 cm)
Package 2 Width	40.00 in (101.6 cm)
Package 2 Length	48.00 in (121.92 cm)
Package 2 Weight	671.00 lb(US) (304.36 kg)

# Offer Sustainability

Sustainable offer status	Green Premium product	
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov	
REACh Regulation	☑REACh Declaration	
REACh free of SVHC	Yes	
EU RoHS Directive	Compliant E EU RoHS Declaration	
Toxic heavy metal free	Yes	
Mercury free	Yes	
China RoHS Regulation	China RoHS Declaration	
RoHS exemption information	₫Yes	
Environmental Disclosure	Product Environmental Profile	
PVC free	Yes	

#### Contractual warranty

Contractad Warranty		
Warranty	18 months	