

HU362NAWK

Safety switch, heavy duty, non fusible, 60A, 3 poles, 60 hp, 600 VAC/DC, NEMA 12, neutral factory installed



Main

Product	Single Throw Safety Switch
Duty Rating	Heavy duty
Device Application	Heavy application
Disconnect Type	Non-fusible disconnect
Factory Installed Neutral	Neutral (factory installed)
Phase	3 phase
Number of Poles	3
Current Rating	60 A
Voltage Rating	600 V AC/DC
Enclosure Rating	NEMA 3R/12
Motor power hp	5 Hp at 120 V AC 50-60 Hz for 1 phase motors 10 Hp at 240 V AC 50-60 Hz for 1 phase motors 20 Hp at 240 V AC 50-60 Hz for 3 phase motors 25 Hp at 480 V AC 50-60 Hz for 1 phase motors 50 Hp at 480 V AC 50-60 Hz for 3 phase motors 30 Hp at 600 V AC 50-60 Hz for 1 phase motors 60 Hp at 600 V AC 50-60 Hz for 3 phase motors 5 Hp at 125 V DC 10 Hp at 250 V DC 30 hp at 600 V DC

Complementary

Mounting Type	Surface
Wiring configuration	4-wire (3PH + N)
Wire Size	AWG 14...AWG 3 copper AWG 12...AWG 3 aluminium
Tightening torque	50 Lbf.in (5.65 N.m) (AWG 3) 45 Lbf.in (5.08 N.m) (AWG 6...AWG 4) 40 Lbf.in (4.52 N.m) 0.01 in ² (8.367 mm ²) (AWG 8) 50 lbf.in (5.65 N.m) 0.00...0.01 in ² (2.06...5.261 mm ²) (AWG 14...AWG 10)
Depth	7.00 in (177.80 mm)
Width	10.5 in (266.70 mm)
Height	16.5 in (419.10 mm)

Environment

Certifications	UL listed file E2875
----------------	----------------------

Ordering and shipping details

Category	00113-H&HU SW,2&3P,N12,30-200A
Discount Schedule	DE1
GTIN	785901666288
Returnability	No
Country of origin	US

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	7.01 in (17.8 cm)
Package 1 Width	10.51 in (26.7 cm)
Package 1 Length	16.50 in (41.9 cm)
Package 1 Weight	17.20 lb(US) (7.802 kg)

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile
PVC free	Yes

Contractual warranty

Warranty	18 months
----------	-----------