H363DS

Safety switch, heavy duty, fusible, 100A, 3 wire, 3 poles, 100hp, 600VAC/DC, Type 4, 4X, 5, 304 stainless steel





Main Product Single Throw Safety Switch **Duty Rating** Heavy duty **Device Application** Heavy application Disconnect Type Fusible disconnect Factory Installed Neutral None Phase 3 phase Number of Poles 3 100 A Current Rating 600 V AC/DC Voltage Rating **Enclosure Rating** NEMA 4/4X/5 stainless steel 304 25 Hp at 480 V AC 50-60 Hz for 3 phase motors Motor power hp

50 hp at 600 V DC

60 Hp at 480 V AC 50-60 Hz for 3 phase motors 30 Hp at 600 V AC 50-60 Hz for 3 phase motors 75 Hp at 600 V AC 50-60 Hz for 3 phase motors

Complementary

Complementary	
Short Circuit Current Rating	10 KA H or K 200 kA R or J
Fuse type	H or K R or J
Mounting Type	Surface
Electrical Connection	Lugs
Wiring configuration	3-wire
Wire Size	AWG 12AWG 1/0 aluminium AWG 14AWG 1/0 copper
Tightening torque	50 Lbf.In (5.65 N.m) (AWG 1AWG 3/0) 45 Lbf.In (5.08 N.m) (AWG 6AWG 4) 40 Lbf.In (4.52 N.m) 0.01 in² (8.367 mm²) (AWG 8) 35 lbf.in (3.95 N.m) 0.0001 in² (2.065.261 mm²) (AWG 14AWG 10)
Depth	6.97 in (177.04 mm)
Width	11.25 in (285.75 mm)
Height	20.82 in (528.83 mm)
Net Weight	22.99 lb(US) (10.43 kg)

Environment

III listed file F2875	

Ordering and shipping details

Category	00010-H&HU SW,2&3P,N4,SS,30-200A
Discount Schedule	DE1
GTIN	785901023708
Returnability	Yes
Country of origin	US

Packing Units

3	
Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	23.60 in (59.944 cm)
Package 1 Width	7.90 in (20.066 cm)
Package 1 Length	11.70 in (29.718 cm)
Package 1 Weight	22.90 lb(US) (10.387 kg)
Unit Type of Package 2	PAL
Number of Units in Package 2	30
Package 2 Height	44.50 in (113.03 cm)
Package 2 Width	40.00 in (101.6 cm)
Package 2 Length	48.00 in (121.92 cm)
Package 2 Weight	707.00 lb(US) (320.69 kg)

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACh Regulation	REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Compliant EPEU RoHS Declaration
Mercury free	Yes
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	₫Yes
Environmental Disclosure	Product Environmental Profile
PVC free	Yes

Contractual warranty

Warranty	18 months