

Product data sheet

Characteristics

8903SQA1V02

Contactor, Type S, multipole lighting,
electrically held, 100A, 2 pole, 110/120 VAC
50/60 Hz coil, NEMA 12



Main

Product	Electrically Held Lighting Contactor
Type	S

Complementary

Control Circuit Voltage	120 V AC 60 Hz 110 V AC 50 Hz
Current Rating	100 A
Number of Poles	2P
Control Units	No control units
Pilot Light	Without pilot light
Auxiliary Contacts	Without
Other Options	None
Electrical Connection	Lugs
Height	31.50 in (800 mm)
Depth	9.25 in (235 mm)
Width	18.15 in (461 mm)

Environment

Enclosure Type	NEMA 12/3R painted sheet steel surface none
Product Certifications	UL Listed CSA

Ordering and shipping details

Category	21325 - 8903 S (NOT S*C) ELECT.
Discount Schedule	CP1
GTIN	785901352846
Returnability	No
Country of origin	MX

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	31.50 in (80.0 cm)
Package 1 Width	18.15 in (46.1 cm)
Package 1 Length	9.25 in (23.5 cm)
Package 1 Weight	9.75 lb(US) (4.424 kg)

Offer Sustainability

REACH Regulation	 REACH Declaration
EU RoHS Directive	Not compliant
China RoHS Regulation	 China RoHS Declaration

Contractual warranty

Warranty	18 months
----------	-----------