Product data sheet Characteristics

9001SKS66B

Selector switch head, Harmony 9001SK, plastic, standard handle, black, 30mm, 3 positions, spring return left to center





Main

Range of Product	Harmony 9001SK
Product or Component Type	Head for selector switch
Device short name	9001SK
Type of operator	Left to centre spring return
Operator profile	Black standard knob

Complementary

Bezel material	Plastic	
Mounting diameter	1.18 in (30 mm)	
Net Weight	0.13 lb(US) (0.059 kg)	
Shape of signaling unit head	Round	
Operator position information	3 positions	
Contacts type and composition	Without contact block	
Mechanical durability	500000 cycles	
Device presentation	Basic element	

Environment

Environment	
Protective treatment	TC
Ambient Air Temperature for Storage	-40158 °F (-4070 °C)
Ambient Air Temperature for Operation	-13158 °F (-2570 °C)
Electrical shock protection class	Class II IEC 61140
IP degree of protection	IP66 IEC 60529
NEMA degree of protection	NEMA 1 NEMA 12 NEMA 13 NEMA 2 NEMA 3 NEMA 3 NEMA 3R NEMA 4 NEMA 4X NEMA 6
Standards	EN/IEC 60947-5-1 EN/IEC 60947-1 CSA C22.2 No 14 UL 508 JIS C 852 JIS C 4520 EN/IEC 60947-5-4
Product Certifications	NEMA UL 508
Vibration resistance	7 gn 2500 Hz)IEC 60068-2-6
Shock resistance	50 gn IEC 60068-2-27

Ordering and shipping details

Category	21429-9001 SK,SKY
Discount Schedule	CS1
GTIN	785901175636
Returnability	No

Packing Units

Unit Type of Package 1	PCE	
Number of Units in Package 1	1	
Package 1 Height	7.62 in (19.355 cm)	
Package 1 Width	3.00 in (7.62 cm)	
Package 1 Length	19.35 in (49.161 cm)	
Package 1 Weight	3.20 oz (90.719 g)	

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Nickel compounds, which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACh Regulation	REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	[™] China RoHS Declaration
RoHS exemption information	₫Yes
Environmental Disclosure	☑ Product Environmental Profile
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.

Contractual warranty

Warranty	18 months	