H322NRB

Safety switch, heavy duty, fusible, 60A, 4 wire, 3 poles, 1 neutral, 15hp, 240VAC/250VDC, Type 3R, bolt on hub provision





Main Product Single Throw Safety Switch **Duty Rating** Heavy duty **Device Application** Heavy application Disconnect Type Fusible disconnect Factory Installed Neutral Neutral (factory installed) Phase 3 phase Number of Poles 3 Current Rating 60 A 250 V DC Voltage Rating 240 V AC **Enclosure Rating** NEMA 3R galvannealed steel Motor power hp 3 Hp at 240 V AC 50-60 Hz for 1 phase motors 7.5 Hp at 240 V AC 50-60 Hz for 3 phase motors 10 Hp at 240 V AC 50-60 Hz for 1 phase motors

10 hp at 250 V DC

15 Hp at 240 V AC 50-60 Hz for 3 phase motors

Complementary

Short Circuit Current Rating	10 KA H or K
· ·	200 kA R or J
Fuse type	H or K
	R or J
Mounting Type	Surface
Electrical Connection	Lugs
Wiring configuration	4-wire (3PH + G)
Wire Size	AWG 14AWG 3 copper
	AWG 12AWG 3 aluminium
Tightening torque	50 Lbf.In (5.65 N.m) (AWG 3)
	45 Lbf.In (5.08 N.m) (AWG 6AWG 4)
	40 Lbf.In (4.52 N.m) 0.01 in ² (8.367 mm ²) (AWG 8)
	50 lbf.in (5.65 N.m) 0.000.01 in² (2.065.261 mm²) (AWG 14AWG 10)
Depth	4.88 in (123.95 mm)
Width	6.63 in (168.40 mm)
Height	14.88 in (377.95 mm)
Net Weight	9.57 lb(US) (4.34 kg)
Net Weight	9.57 lb(US) (4.34 kg)

Environment

Certifications	UL listed file E2875

Ordering and shipping details

00009-H&HU SW,2&3P,N3R,30-200A
DE1
785901480211
Yes
US
_

Packing Units

3	
Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	5.40 in (13.716 cm)
Package 1 Width	7.80 in (19.812 cm)
Package 1 Length	17.40 in (44.196 cm)
Package 1 Weight	8.60 lb(US) (3.901 kg)
Unit Type of Package 2	PAL
Number of Units in Package 2	120
Package 2 Height	46.00 in (116.84 cm)
Package 2 Width	40.00 in (101.6 cm)
Package 2 Length	48.00 in (121.92 cm)
Package 2 Weight	1052.00 lb(US) (477.179 kg)

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACh Regulation	☑ REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Compliant EEU RoHS Declaration
Mercury free	Yes
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	₽¥Yes
Environmental Disclosure	
PVC free	Yes

Contractual warranty

Warranty	18 months