# 9001K43J1G

Illuminated selector switch head, Harmony 9001K, metal, standard handle, green, 30mm, 3 positions, stay put, 110-120V





Main	
Product or Component Type	Head for illuminated selector switch
Device short name	K
Enclosure type	Dust and oil resistant weatherproof enclosure indoor/outdoor
Mounting diameter	1.18 in (30 mm)
Range of Product	Harmony 9001K

Complementary

Bulb base BA 9s  Contacts type and composition Without contact block  Light block supply Via transformer 120 V AC 50/60 Hz Via transformer 110 V AC 50/60 Hz  Operator position information 3 positions  Operator profile Standard handle  Operator profile 1 projecting push-button  Size 30 mm  Type of operator Waintained  Cap/operator or lens colour Green  [Us] rated supply voltage 110120 V  Light block supply Via integral transformer  Type of operator Stay put			
Contacts type and composition  Without contact block  Light block supply  Via transformer 120 V AC 50/60 Hz  Via transformer 110 V AC 50/60 Hz  Operator position information  3 positions  Operator profile  Standard handle  Operator profile  1 projecting push-button  Size  30 mm  Type of operator  Maintained  Cap/operator or lens colour  Green  [Us] rated supply voltage  110120 V  Light block supply  Via integral transformer  Type of operator  Stay put	Bezel material	Metal	
Light block supply  Via transformer 120 V AC 50/60 Hz Via transformer 110 V AC 50/60 Hz Operator position information  3 positions Operator profile  Standard handle Operator profile  1 projecting push-button Size  30 mm  Type of operator  Maintained Cap/operator or lens colour  Green  [Us] rated supply voltage  Light block supply  Via integral transformer  Type of operator  Stay put	Bulb base	BA 9s	
Via transformer 110 V AC 50/60 Hz Operator position information 3 positions Operator profile Standard handle Operator profile 1 projecting push-button Size 30 mm Type of operator Maintained Cap/operator or lens colour Green [Us] rated supply voltage 110120 V Light block supply Via integral transformer Type of operator Stay put	Contacts type and composition	Without contact block	
Operator profile Operator profile 1 projecting push-button Size 30 mm Type of operator Maintained Cap/operator or lens colour [Us] rated supply voltage Light block supply Type of operator Stay put  Standard handle 1 projecting push-button  Maintained  Green  Stay put	Light block supply		
Operator profile 1 projecting push-button Size 30 mm  Type of operator Maintained Cap/operator or lens colour Green [Us] rated supply voltage 110120 V  Light block supply Via integral transformer Type of operator Stay put	Operator position information	3 positions	
Size 30 mm  Type of operator Maintained  Cap/operator or lens colour Green  [Us] rated supply voltage 110120 V  Light block supply Via integral transformer  Type of operator Stay put	Operator profile	Standard handle	
Type of operator  Maintained  Cap/operator or lens colour  [Us] rated supply voltage  110120 V  Light block supply  Via integral transformer  Type of operator  Stay put	Operator profile	1 projecting push-button	
Cap/operator or lens colour  [Us] rated supply voltage  Light block supply  Via integral transformer  Type of operator  Stay put	Size	30 mm	
[Us] rated supply voltage 110120 V  Light block supply Via integral transformer  Type of operator Stay put	Type of operator	Maintained	
Light block supply Via integral transformer  Type of operator Stay put	Cap/operator or lens colour	Green	
Type of operator Stay put	[Us] rated supply voltage	110120 V	
	Light block supply	Via integral transformer	
Contacts type and composition Without contact block	Type of operator	Stay put	
	Contacts type and composition	Without contact block	

#### Environment

NEMA degree of protection	NEMA 1/2/3/3R/4/6/12/13
Product Certifications	CSA LR24590 class 3211 03 CE UL listed file E42259 CCN NKCR

#### Ordering and shipping details

Category	21426-9001 K (NOT KA,KM,KX)
Discount Schedule	CS1
GTIN	785901350699
Returnability	No

# Packing Units

Unit Type of Package 1	PCE	
Number of Units in Package 1	1	
Package 1 Height	5.08 in (12.903 cm)	
Package 1 Width	2.00 in (5.08 cm)	
Package 1 Length	12.90 in (32.774 cm)	
Package 1 Weight	8.80 oz (249.476 g)	

### Offer Sustainability

Sustainable offer status	Green Premium product	
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cance and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov	
REACh Regulation	☑ REACh Declaration	
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS  Declaration	
Mercury free	Yes	
China RoHS Regulation	China RoHS Declaration	
RoHS exemption information	₽¥Yes	
Environmental Disclosure	Product Environmental Profile	
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.	

### Contractual warranty

Warranty	18 months	