

# HU362AWKVW

Safety switch, heavy duty, non fusible, 60A,  
3 poles, 60hp, 600VAC/DC, Type 12, viewing  
window



## Main

|                           |                                                                                                                                                                                                                                                                                                                                              |
|---------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Product                   | Single Throw Safety Switch                                                                                                                                                                                                                                                                                                                   |
| Duty Rating               | Heavy duty                                                                                                                                                                                                                                                                                                                                   |
| Device Application        | Heavy application                                                                                                                                                                                                                                                                                                                            |
| Disconnect Type           | Non-fusible disconnect                                                                                                                                                                                                                                                                                                                       |
| Factory Installed Neutral | None                                                                                                                                                                                                                                                                                                                                         |
| Phase                     | 3 phase                                                                                                                                                                                                                                                                                                                                      |
| Number of Poles           | 3                                                                                                                                                                                                                                                                                                                                            |
| Current Rating            | 60 A                                                                                                                                                                                                                                                                                                                                         |
| Voltage Rating            | 600 V AC/DC                                                                                                                                                                                                                                                                                                                                  |
| Enclosure Rating          | NEMA 3R/12                                                                                                                                                                                                                                                                                                                                   |
| Motor power hp            | 10 Hp at 240 V AC 50-60 Hz for 1 phase motors<br>20 Hp at 240 V AC 50-60 Hz for 3 phase motors<br>25 Hp at 480 V AC 50-60 Hz for 1 phase motors<br>50 Hp at 480 V AC 50-60 Hz for 3 phase motors<br>30 Hp at 600 V AC 50-60 Hz for 1 phase motors<br>60 Hp at 600 V AC 50-60 Hz for 3 phase motors<br>10 Hp at 250 V DC<br>30 hp at 600 V DC |

## Complementary

|                      |                                                                                                                                                                                                                                                          |
|----------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Mounting Type        | Surface                                                                                                                                                                                                                                                  |
| Wiring configuration | 3-wire                                                                                                                                                                                                                                                   |
| Wire Size            | AWG 14...AWG 3 copper<br>AWG 12...AWG 3 aluminium                                                                                                                                                                                                        |
| Tightening torque    | 50 Lbf.In (5.65 N.m) (AWG 3)<br>45 Lbf.In (5.08 N.m) (AWG 6...AWG 4)<br>40 Lbf.In (4.52 N.m) 0.01 in <sup>2</sup> (8.367 mm <sup>2</sup> ) (AWG 8)<br>50 lbf.in (5.65 N.m) 0.00...0.01 in <sup>2</sup> (2.06...5.261 mm <sup>2</sup> ) (AWG 14...AWG 10) |
| Depth                | 7 in (177.80 mm)                                                                                                                                                                                                                                         |
| Width                | 10.5 in (266.70 mm)                                                                                                                                                                                                                                      |
| Height               | 16.5 in (419.10 mm)                                                                                                                                                                                                                                      |
| Net Weight           | 17.64 lb(US) (8 kg)                                                                                                                                                                                                                                      |

## Environment

|                |                      |
|----------------|----------------------|
| Certifications | UL listed file E2875 |
|----------------|----------------------|

## Ordering and shipping details

|                   |                               |
|-------------------|-------------------------------|
| Category          | 00117-H&HU SW,VIEW WINDOW(VW) |
| Discount Schedule | DE1                           |
| GTIN              | 785901208877                  |
| Returnability     | No                            |
| Country of origin | US                            |

## Packing Units

|                              |                         |
|------------------------------|-------------------------|
| Unit Type of Package 1       | PCE                     |
| Number of Units in Package 1 | 1                       |
| Package 1 Height             | 19.70 in (50.038 cm)    |
| Package 1 Width              | 7.40 in (18.796 cm)     |
| Package 1 Length             | 10.90 in (27.686 cm)    |
| Package 1 Weight             | 17.45 lb(US) (7.915 kg) |

## Offer Sustainability

|                            |                                                                                                                                                                                                                                                                                             |
|----------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Sustainable offer status   | Green Premium product                                                                                                                                                                                                                                                                       |
| California proposition 65  | WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a> |
| REACH Regulation           | <a href="#">REACH Declaration</a>                                                                                                                                                                                                                                                           |
| REACH free of SVHC         | Yes                                                                                                                                                                                                                                                                                         |
| EU RoHS Directive          | Compliant <a href="#">EU RoHS Declaration</a>                                                                                                                                                                                                                                               |
| Mercury free               | Yes                                                                                                                                                                                                                                                                                         |
| China RoHS Regulation      | <a href="#">China RoHS Declaration</a>                                                                                                                                                                                                                                                      |
| RoHS exemption information | <a href="#">Yes</a>                                                                                                                                                                                                                                                                         |
| Environmental Disclosure   | <a href="#">Product Environmental Profile</a>                                                                                                                                                                                                                                               |
| PVC free                   | Yes                                                                                                                                                                                                                                                                                         |

## Contractual warranty

|          |           |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|