# HU365RVW

Factory Installed Neutral

Safety switch, heavy duty, non fusible, 400A, 3 poles, 350hp, 600VAC/DC, NEMA 3R, viewing window





# MainProductSingle Throw Safety SwitchDuty RatingHeavy dutyDevice ApplicationHeavy applicationDisconnect TypeNon-fusible disconnect

None

Phase	3 phase
Number of Poles	3
Current Rating	400 A
Voltage Rating	600 V AC/DC
Enclosure Rating	NEMA 3R galvannealed steel
Motor power hp	125 Hp at 240 V AC 50-60 Hz for 3 phase motors 250 Hp at 480 V AC 50-60 Hz for 3 phase motors 350 Hp at 600 V AC 50-60 Hz for 3 phase motors 50 Hp at 250 V DC 50 hp at 600 V DC

## Complementary

Surface	
3-wire	
AWG 1/0750 kcmil copper or aluminium	
550 lbf.in (62.14 N.m) (AWG 1/0750 kcmil)	
10.13 in (257.30 mm)	
27.88 in (708.15 mm)	
50.31 in (1277.87 mm)	
	3-wire  AWG 1/0750 kcmil copper or aluminium  550 lbf.in (62.14 N.m) (AWG 1/0750 kcmil)  10.13 in (257.30 mm)  27.88 in (708.15 mm)

#### Environment

Certifications	UL listed file E2875

## Ordering and shipping details

Category	00054-H&HU SW,NEMA3R,400-1200A
Discount Schedule	DE1
GTIN	785901693543
Returnability	No
Country of origin	US

## **Packing Units**

PCE	
1	
50.31 in (127.8 cm)	
27.87 in (70.8 cm)	
10.12 in (25.7 cm)	
176.00 lb(US) (79.832 kg)	
	1 50.31 in (127.8 cm) 27.87 in (70.8 cm) 10.12 in (25.7 cm)

# Offer Sustainability

Warranty

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACh Regulation	☑ REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Compliant EPEU RoHS Declaration
Mercury free	Yes
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	₫Yes
Environmental Disclosure	Product Environmental Profile
PVC free	Yes
Halogen content performance	Halogen free plastic parts product

18 months