9001KS11K1E25

Key selector switch head, Harmony 9001K, metal, key switch, 30mm, key E25, 2 positions, stay put





Main

| TTT CALL | |
|------------------------------|------------------------------|
| Range of Product | Harmony 9001K |
| Product or Component Type | Head for key selector switch |
| Device short name | 9001KS |
| Type of operator | maintained |
| Operator profile | Black key switch |
| | |

Complementary

| Metal | |
|------------------------|--|
| 1.18 in (30 mm) | |
| 0.54 lb(US) (0.245 kg) | |
| Round | |
| 2 positions | |
| E25 | |
| Left | |
| Without contact block | |
| 500000 cycles | |
| Basic element | |
| Key switch | |
| Stay put | |
| 30 mm | |
| 5 | |
| | 1.18 in (30 mm) 0.54 lb(US) (0.245 kg) Round 2 positions E25 Left Without contact block 500000 cycles Basic element Key switch Stay put 30 mm |

Environment

| Protective treatment | TC |
|---------------------------------------|--|
| Ambient Air Temperature for Storage | -40158 °F (-4070 °C) |
| Ambient Air Temperature for Operation | -13158 °F (-2570 °C) |
| Overvoltage category | Class II IEC 61140 |
| IP degree of protection | IP66 IEC 60529 |
| NEMA degree of protection | NEMA 1 NEMA 12 NEMA 13 NEMA 2 NEMA 3 NEMA 3 NEMA 3R NEMA 4 NEMA 6 |
| Standards | CSA C22.2 No 14 EN/IEC 60947-5-1 EN/IEC 60947-1 UL 508 EN/IEC 60947-5-4 JIS C 4520 JIS C 852 |

| Product Cartifications | NΕMA |
|-------------------------------|--|
| Product Certifications | NEMA UL 508 |
| Vibration resistance | 7 gn 2500 Hz)IEC 60068-2-6 |
| Shock resistance | 50 gn IEC 60068-2-27 |
| Ordering and shipping details | |
| Category | 21426-9001 K (NOT KA,KM,KX) |
| Discount Schedule | CS1 |
| GTIN | 785901732358 |
| Returnability | No |
| | |
| Packing Units | |
| Unit Type of Package 1 | PCE . |
| Number of Units in Package 1 | 1 |
| Package 1 Height | 2.00 in (5.08 cm) |
| Package 1 Width | 2.00 in (5.08 cm) |
| Package 1 Length | 3.50 in (8.89 cm) |
| Package 1 Weight | 8.93 oz (253.105 g) |
| Offer Sustainability | |
| Sustainable offer status | Green Premium product |
| California proposition 65 | WARNING: This product can expose you to chemicals including: Nickel compounds, which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov |
| REACh Regulation | REACh Declaration |
| EU RoHS Directive | Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration |
| Mercury free | Yes |
| China RoHS Regulation | ☐ China RoHS Declaration |
| RoHS exemption information | ₽ |
| Environmental Disclosure | Product Environmental Profile |
| WEEE | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins. |

Contractual warranty

| Contracted warranty | | |
|---------------------|-----------|--|
| Warranty | 18 months | |