# QO220EPD1200

Mini circuit breaker, QO, 20A, 2 pole, 120/240VAC, 10kA, 30mA grd fault B, plug in mount, aux switch 1A





#### Main

Product	Miniature circuit-breaker
Range	QO
Current Rating	20 A
Voltage Rating	120/240 V AC 120 V AC
Mounting Type	Plug-in
Number of Poles	2P
Circuit Breaker Type	Ground fault protecting class B 30 mA
Ratings	Not rated
Electrical Connection	Pressure plate
Options	Auxiliary switch 120 V AC 1A

### Complementary

Interrupt Rating	10 KA 120/240 V AC 50/60 Hz 10 kA 120 V AC 50/60 Hz
Number of Panel Spaces	3
Wire Size	AWG 14AWG 8 copper AWG 12AWG 8 aluminium
Tightening Torque	40.71 Lbf.In (4.6 N.m) 0.000.02 in² (2.510 mm²) (AWG 16AWG 14) 40.71 lbf.in (4.6 N.m) 0.010.03 in² (420 mm²) (AWG 12AWG 4)
Height	4.13 in (105 mm)
Width	2.24 in (57 mm)
Depth	2.91 in (74 mm)
Net Weight	1.13 lb(US) (0.513 kg)

#### **Environment**

Certifications	UL Listed CSA
Ambient Rating	104 °F (40 °C)

## Ordering and shipping details

Category	00910-QO-EPD,QOB-EPD BREAKERS
Discount Schedule	DE2A
GTIN	785901667230
Returnability	No
Country of origin	MX

#### **Packing Units**

PCE	
1	
2.25 in (5.715 cm)	
3.25 in (8.255 cm)	
4.87 in (12.37 cm)	
18.08 oz (512.559 g)	
	1 2.25 in (5.715 cm) 3.25 in (8.255 cm) 4.87 in (12.37 cm)

# Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: DINP, which is known to the State of California to cause cancer, and DIDP, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACh Regulation	REACh Declaration
EU RoHS Directive	Compliant EEU RoHS Declaration
Mercury free	Yes
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	€Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End Of Life Information

#### Contractual warranty

Warranty	18 months