

Product data sheet

Characteristics

8903SQW22V02

Contactor, Type S, multipole lighting,
electrically held, 100A, 3 pole, 110/120 VAC
50/60 Hz coil, NEMA 4/4X



Main

Product	Electrically Held Lighting Contactor
Type	S

Complementary

Control Circuit Voltage	120 V AC 60 Hz 110 V AC 50 Hz
Current Rating	100 A
Number of Poles	3P
Control Units	No control units
Pilot Light	Without pilot light
Auxiliary Contacts	Without
Other Options	None
Electrical Connection	Lugs
Height	33.50 in (851 mm)
Depth	11.93 in (303 mm)
Width	25.83 in (656 mm)

Environment

Enclosure Type	NEMA 4/4X glass polyester surface none
Product Certifications	UL Listed CSA

Ordering and shipping details

Category	21325 - 8903 S (NOT S*C) ELECT.
Discount Schedule	CP1
GTIN	785901971634
Returnability	No
Country of origin	MX

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	33.50 in (85.1 cm)
Package 1 Width	25.83 in (65.6 cm)
Package 1 Length	11.93 in (30.3 cm)
Package 1 Weight	53.88 lb(US) (24.44 kg)

Offer Sustainability

California proposition 65	WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov
REACH Regulation	 REACH Declaration
EU RoHS Directive	Not compliant
China RoHS Regulation	 China RoHS Declaration

Contractual warranty

Warranty	18 months
----------	-----------