

Product data sheet

Characteristics

8903SVO4V02

Contactor, Type S, multipole lighting,
electrically held, 200A, 5 pole, 110/120 VAC
50/60 Hz coil, open style



Main

Product	Electrically Held Lighting Contactor
Type	S

Complementary

Control Circuit Voltage	120 V AC 60 Hz 110 V AC 50 Hz
Current Rating	200 A
Number of Poles	5P
Control Units	No control units
Pilot Light	Without pilot light
Auxiliary Contacts	Without
Other Options	None
Electrical Connection	Lugs
Height	9.13 in (232 mm)
Depth	6.50 in (165 mm)
Width	9.76 in (248 mm)

Environment

Enclosure Type	Not rated (open device) surface none
Product Certifications	UL Listed CSA

Ordering and shipping details

Category	21325 - 8903 S (NOT S*C) ELECT.
Discount Schedule	CP1
GTIN	785901601609
Returnability	No
Country of origin	MX

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	9.13 in (23.2 cm)
Package 1 Width	9.76 in (24.8 cm)
Package 1 Length	6.50 in (16.5 cm)
Package 1 Weight	16.70 lb(US) (7.575 kg)

Offer Sustainability

EU RoHS Directive	Not compliant
China RoHS Regulation	 China RoHS Declaration

Contractual warranty

Warranty	18 months
----------	-----------