



TERMINAL LUG DATA ‡			
AMPERES	MAX WIRE	MIN WIRE	TYPE
60	#3 AWG	#12 AWG	AL
60	#3 AWG	#14 AWG	CU

DUAL DIMENSIONS: INCHES  
MILLIMETERS

NOTES:  
FINISH - TYPE 316 STAINLESS STEEL  
UL LISTED - E2875  
CSA - FILE PER REFERENCE 158337 REPORT 1100884 (LL 89067-16).  
ALL NEUTRALS - INSULATED  
SHORT CIRCUIT CURRENT RATINGS:  
10,000 RMS SYMMETRICAL AMPERES  
WHEN USED IN CONJUNCTION  
WITH CLASS H OR K FUSES  
200,000 RMS SYMMETRICAL AMPERES WHEN USED  
IN CONJUNCTION WITH CLASS R, J OR T FUSES  
\* USE BOTH OUTER SWITCHING POLES  
♦ IF CORNER GROUNDED DELTA SYSTEM, INSTALL NEUTRAL AND USE OUTER SWITCHING  
POLES FOR UNGROUNDED CONDUCTORS.  
‡ LUGS SUITABLE FOR 60°C OR 75°C CONDUCTORS ONLY.

CATALOG NUMBER	VOLTAGE RATINGS	AMPERAGE RATINGS	WIRING DIAG	HORSEPOWER RATINGS																250 VDC		600 VDC			
				240VAC						480VAC						600VAC									
				STD			MAX			STD			MAX			STD			MAX						
				1Ø	2Ø	3Ø	1Ø	2Ø	3Ø	1Ø	2Ø	3Ø	1Ø	2Ø	3Ø	1Ø	2Ø	3Ø	STD	MAX	STD	MAX			
H362SS	600VAC,600VDC	60	A	—	—	—	—	—	—	5*	—	15 ♦	20*	—	30 ♦	—	—	15	—	50	—	—	25	30	
HU362SS	600VAC,600VDC	60	B	—	—	—	10*	—	15 ♦	—	—	—	25*	—	30 ♦	—	—	—	30*	—	60	—	10*	—	30*

HEAVY DUTY SAFETY SWITCHES  
VISIBLE BLADES  
60 AMPERE-SERIES F6  
ENCLOSURE-NEMA TYPE 4, 4X AND 5 STAINLESS STEEL



DWG# 3333  
NO.