8538SCW24V02S

NEMA Combination Starter, Type S, 30A fusible disconnect, Size 1, 27A, 10 HP at 600 VAC polyphase, 120 VAC coil, NEMA 4X



Main

Product	Combination Starter
Туре	S
Control Circuit Type	Separate control circuit

Complementary

Complementary		
Control Circuit Voltage	110 V AC 50 Hz	
	120 V AC 60 Hz	
Starter Type	Non reversing	
Number of Poles	3P	
Horsepower Rating	10 Hp 460 V AC, 3 phase	
	10 hp 575 V AC, 3 phase	
Maximum Voltage Rating	600 V AC	
Control Units	No control units	
Pilot Light	No indicator	
Auxiliary Contacts	Without	
Thermal overload type	Melting alloy 3	
Disconnect Type	Fusible disconnect switch H, 30 A	
NEMA size	1	

Environment

Enclosure Type	NEMA 4X glass polyester with external reset
Liiciosure rype	NLIVIA 4A glass pulyester with external reset

Ordering and shipping details

Category	21217 - 8538,39 S*R,S*T,S*W
Discount Schedule	CP1
GTIN	785901163381
Returnability	Yes
Country of origin	MX

Packing Units

Unit Type of Package 1	PCE	_
Number of Units in Package 1	1	_
Package 1 Weight	45.00 lb(US) (20.412 kg)	

Offer Sustainability

EU RoHS Directive	Not compliant	
China RoHS Regulation	China RoHS Declaration	

Warranty 18 months