

Product data sheet

Characteristics

8903SYG17V02

Contactor, Type S, multipole lighting,
mechanically held, 400A, 3 pole, 110/120 VAC
50/60 Hz coil, NEMA 1



Main

Product	Mechanically Held Lighting Contactor
Type	S

Complementary

Control Circuit Voltage	120 V AC 60 Hz 110 V AC 50 Hz
Current Rating	400 A
Number of Poles	3P
Control Units	No control units
Pilot Light	Without pilot light
Auxiliary Contacts	Without
Other Options	None
Electrical Connection	Lugs
Height	65.75 in (1670 mm)
Depth	13.11 in (333 mm)
Width	20.20 in (513 mm)

Environment

Enclosure Type	NEMA 1 painted sheet steel surface none
Product Certifications	UL Listed CSA

Ordering and shipping details

Category	30156-8903 S:ELEC HELD LTG CONTR
Discount Schedule	SQ2L
GTIN	785901113621
Returnability	No
Country of origin	US

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	65.75 in (167.0 cm)
Package 1 Width	20.20 in (51.3 cm)
Package 1 Length	13.11 in (33.3 cm)
Package 1 Weight	227.00 lb(US) (102.966 kg)

Offer Sustainability

California proposition 65	WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov
REACH Regulation	 REACH Declaration
EU RoHS Directive	Not compliant
China RoHS Regulation	 China RoHS Declaration

Contractual warranty

Warranty	18 months
----------	-----------