8502SEO2V02SX10

NEMA Contactor, Type S, nonreversing, Size 3, 90A, 50 HP at 575 VAC, 3 phase, up to 100 kA, 3 pole, 120 VAC coil, open



Main

Product Type	Contactor
Product Range	8502S
Contactor Type	Non-reversing

Complementary

Complementary		
NEMA Size	3	
Rated Current	90 A	
Number of Poles	3P	
Maximum Voltage Rating	600 V AC	
Phase	3 phase	
Horsepower Rating	25 HP 200 V AC 30 HP 230 V AC 50 HP 460 V AC 50 HP 575 V AC	
SCCR	Circuit-breaker 150 A maximum, SCCR: 100 kA at 480 V AC Fuse J 200 A maximum, SCCR: 100 kA at 600 V AC Fuse T 200 A maximum, SCCR: 100 kA at 600 V AC Fuse RK1 200 A maximum, SCCR: 100 kA at 600 V AC Fuse RK5 200 A maximum, SCCR: 100 kA at 600 V AC	
Coil Voltage	120 V AC 60 Hz 110 V AC 50 Hz	
Control Circuit Type	Separate control circuit	
Control Units	No control units	
Pilot Light	No indicator	
Auxiliary Contacts	1 NO	
Other Equipment	Fuse not supplied	
Terminal Type	Screw clamp terminals	
Height	7.09 in (180.09 mm)	
Width	5.98 in (151.94 mm)	
Depth	6.50 in (165.10 mm)	

Environmental

Enclosure Type	Not rated (open device)
Certifications	UL listed file E78351 CCN NLDX CSA

Ordering and shipping details

Category	21193 - 8502,36 SE,SF(NOT S*R,T,W)
Discount Schedule	CP1
GTIN	785901603849
Returnability	No
Country of origin	MX

Packing Units

3	
Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	7.09 in (18.0 cm)
Package 1 Width	5.98 in (15.2 cm)
Package 1 Length	6.50 in (16.5 cm)
Package 1 Weight	14.00 lb(US) (6.35 kg)

Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACh Regulation	REACh Declaration
EU RoHS Directive	Not compliant
China RoHS Regulation	☑ China RoHS Declaration

Contractual warranty

Warranty	19 months
vvarianty	18 months