# 8702SEO1V06

NEMA Contactor, Type S, reversing, vertical, Size 3, 90A, 50 HP at 575 VAC, 3 phase, up to 100 kA, 3 pole, 480 VAC coil, open style



### Main

Product Type	Contactor	
Product Range	Type S	
Contactor Type	Reversing	

Complementary

Complementary		
NEMA Size	3	
Rated Current	90 A	
Number of Poles	3P	
Mounting Orientation	Vertical	
Wiring Mode	3 wires	
Maximum Voltage Rating	600 V AC	
Phase	3 phase	
Horsepower Rating	25 HP 200 V AC 30 HP 230 V AC 50 HP 460 V AC 50 HP 575 V AC	
SCCR	Circuit-breaker 150 A maximum, SCCR: 100 kA at 480 V AC Fuse J 200 A maximum, SCCR: 100 kA at 600 V AC Fuse T 200 A maximum, SCCR: 100 kA at 600 V AC Fuse RK1 200 A maximum, SCCR: 100 kA at 600 V AC Fuse RK5 200 A maximum, SCCR: 100 kA at 600 V AC	
Coil Voltage	440 V AC 50 Hz 480 V AC 60 Hz	
Control Circuit Type	Common control circuit	
Control Units	No control units	
Pilot Light	No indicator	
Other Equipment	Fuse not supplied	
Terminal Type	Screw clamp terminals	
Height	19.00 in (482.60 mm)	
Width	7.20 in (183 mm)	
Depth	7.00 in (177.80 mm)	

### Environment

Enclosure Type	Not rated (open device)
Certifications	UL Listed CSA

# Ordering and shipping details

21273 - 8702,36 SE,SF(NOT S*R,T,W)
CP1
785901220855
No
MX

# Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	19.02 in (48.3 cm)
Package 1 Width	7.20 in (18.3 cm)
Package 1 Length	7.01 in (17.8 cm)
Package 1 Weight	17.00 lb(US) (7.711 kg)

# Offer Sustainability

EU RoHS Directive	Not compliant
China RoHS Regulation	China RoHS Declaration

# Contractual warranty

Warranty 1	18 months
------------	-----------