# HOM115AFI

Mini circuit breaker, Homeline, 15A, 1 pole, 120VAC, 10kA AIR, ARC fault, pigtail neutral, plug in, UL





#### Main

| Product                         | Miniature circuit-breaker      |
|---------------------------------|--------------------------------|
| Range                           | Homeline                       |
| Current Rating                  | 15 A                           |
| Certifications                  | UL Listed                      |
| Voltage Rating                  | 120 V AC                       |
| Mounting Type                   | Plug-in                        |
| Number of Poles                 | 1P                             |
| Short Circuit Current<br>Rating | 10 kA                          |
| Number of Spaces                | 1                              |
| Circuit Breaker Type            | ARC-fault                      |
| Ratings                         | HACR rated                     |
| Electrical Connection           | Screw clamp terminals          |
| Wire Size                       | AWG 14AWG 8 aluminium/copper)1 |

#### Complementary

| Tightening torque | 35.40 lbf.in (4.0 N.m) 0.000.01 in² (2.56 mm²) (AWG 14AWG 8) | _ |
|-------------------|--|---|
| Height            | 3.13 in (79.50 mm)   |   |
| Width             | 1 in (25.40 mm)  |   |
| Depth             | 2.98 in (75.69 mm)   | _ |

#### **Environment**

| Ambient Air Temperature for Operation   | 104 °F (40 °C) |
|---|----------------|
| Allibient All Temperature for Operation | 104 1 (40 0)   |

#### Ordering and shipping details

| Category          | 06301-HOM SINGLE POLE ARC FAULT CIRCUIT BREAKER |
|-------------------|---|
| Discount Schedule | DE3D  |
| GTIN              | 785901301318                                    |
| Returnability     | Yes   |
| Country of origin | MX  |

### **Packing Units**

| Unit Type of Package 1       | PCE                      |
|------------------------------|--------------------------|
| Number of Units in Package 1 | 1                        |
| Package 1 Height             | 1.30 in (3.302 cm)       |
| Package 1 Width              | 3.90 in (9.906 cm)       |
| Package 1 Length             | 5.50 in (13.97 cm)       |
| Package 1 Weight             | 10.24 oz (290.299 g)     |
| Unit Type of Package 2       | CAR                      |
| Number of Units in Package 2 | 38                       |
| Package 2 Height             | 4.00 in (10.16 cm)       |
| Package 2 Width              | 14.00 in (35.56 cm)      |
| Package 2 Length             | 21.00 in (53.34 cm)      |
| Package 2 Weight             | 24.52 lb(US) (11.122 kg) |

| Unit Type of Package 3       | PAL                         |  |
|------------------------------|-----------------------------|--|
| Number of Units in Package 3 | 1824                        |  |
| Package 3 Height             | 40.00 in (101.6 cm)         |  |
| Package 3 Width              | 40.00 in (101.6 cm)         |  |
| Package 3 Length             | 48.00 in (121.92 cm)        |  |
| Package 3 Weight             | 1177.00 lb(US) (533.878 kg) |  |

## Offer Sustainability

| Sustainable offer status    | Green Premium product  |
|-----------------------------|--|
| California proposition 65   | WARNING: This product can expose you to chemicals including: DINP, which is known to the State of California to cause cancer, and DIDP, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov |
| REACh Regulation            | REACh Declaration  |
| EU RoHS Directive           | Compliant  |
| Mercury free                | Yes  |
| RoHS exemption information  | ₫Yes   |
| China RoHS Regulation       | China RoHS Declaration   |
| Environmental Disclosure    | Product Environmental Profile  |
| Circularity Profile         | End Of Life Information  |
| Halogen content performance | Halogen free product   |

#### Contractual warranty

| Contractual warranty |          |  |
|----------------------|----------|--|
| Warranty             | Lifetime |  |