# 8536SCO3V08E

NEMA Motor Starter, Type S, nonreversing, Size 1, 27A, 10 HP at 460 VAC, up to 65 kA SCCR, 3 phase, 3 pole, bimetal, 208 VAC coil, open



#### Main

Product Type	Motor starter
Product Range	S
Starter Type	Non reversing

Complementary

NEMA Size	1	
Rated Current	27 A	
Number of Poles	3P	
Maximum Voltage Rating	600 V AC	
Phase	3 phase	
Type of Overload	IEC adapted Bi-metal	
Horsepower Rating	7.5 HP 200 V AC 7.5 HP 230 V AC 10 HP 460 V AC 10 HP 575 V AC	
SCCR	Circuit-breaker 60 A maximum, SCCR: 65 kA at 480 V AC Circuit-breaker 60 A maximum, SCCR: 50 kA at 600 V AC Fuse J 80 A maximum, SCCR: 65 kA at 600 V AC Fuse CC 80 A maximum, SCCR: 65 kA at 600 V AC	
Coil Voltage	208 V AC 60 Hz	
Control Circuit Type	Separate control circuit	
Control Units	No control units	
Pilot Light	Without pilot light	
Auxiliary Contacts	Without	
Terminal Type	Screw clamp terminals	
Height	6.81 in (172.96 mm)	
Width	3.50 in (88.90 mm)	
Depth	4.22 in (107.19 mm)	

#### Environment

Enclosure Type	Not rated (open device)
Certifications	UL Listed CSA NEMA

# Ordering and shipping details

Category	21192 - 8502,36 SC,SD(NOT S*R,T,W)
Discount Schedule	CP1
GTIN	785901526094
Returnability	Yes
Country of origin	MX

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	4.80 in (12.192 cm)
Package 1 Width	6.00 in (15.24 cm)
Package 1 Length	8.00 in (20.32 cm)
Package 1 Weight	3.50 lb(US) (1.588 kg)

## Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACh Regulation	☐ REACh Declaration
EU RoHS Directive	Not compliant
China RoHS Regulation	☑ China RoHS Declaration
PVC free	Yes

### Contractual warranty

Contractical Warranty	
Warranty	18 months