9001KT1R6

Push-to-test pilot light, Harmony 9001K, metal, glass, domed, red, 30mm, 110-120V





Main

Mairi	
Range of Product	Harmony 9001K
Product or Component Type	Push-to-test pilot light
Device short name	К

Complementary

Bezel material	Metal
Mounting diameter	1.18 in (30 mm)
Lens type	Domed glass
Cap/operator or lens colour	Red
Bulb base	BA 9s
Light block supply	Via transformer 110 V AC 50/60 Hz Via transformer 120 V AC 50/60 Hz
Shape of screw head	Round
Light source	Incandescent bulb
Operating Mode	Push-to-test
Lens type	Domed
[Us] rated supply voltage	110120 V
Light block supply	Via integral transformer
Contacts type and composition	1 C/O
Supply frequency	5060 Hz
Lens material	Glass
Size	30 mm

Environment

Product Certifications	CE CSA LR25490 class 3211 03 UL listed file E42259 CCN NKCR
NEMA degree of protection	NEMA 1/2/3/3R/4/6/12/13

Ordering and shipping details

Category	21426-9001 K (NOT KA,KM,KX)
Discount Schedule	CS1
GTIN	785901170334
Returnability	No

Packing Units

Unit Type of Package 1	PCE	
Number of Units in Package 1	1	
Package 1 Height	3.81 in (9.677 cm)	
Package 1 Width	1.50 in (3.81 cm)	
Package 1 Length	9.68 in (24.581 cm)	
Package 1 Weight	9.44 oz (267.62 g)	

Offer Sustainability

Green Premium product
WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACh Declaration
Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Yes
China RoHS Declaration
€Yes
Product Environmental Profile
The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.

Contractual warranty

Warranty	18 months